Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No.



453/2010 Revision date: 30/12/2015

Date of issue: 15/08/2013

Version: 3.1

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form Mixture Product Name MED10-6605 **RTV** Cure Silicone Dispersion Synonyms 1.2. Relevant identified uses of the substance or mixture and uses advised against 1.2.1. Relevant identified uses Use of the substance/mixture Improves the adhesion of addition-cured systems to various substrates. For professional use only.

#### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

NuSil Technology LLC 1050 Cindy Lane Carpinteria, California 93013 USA (805) 684-8780 ehs@nusil.com www.nusil.com

#### 1.4. Emergency telephone number

Emergency : 800-424-9300 CHEMTREC (in US); +1 703-527-3887 CHEMTREC (International and number Maritime)

## **SECTION 2: Hazards identification**

2.1. Classification of the subst Classification according to Regul	
Flam. Liq. 3	H226
Acute Tox. 4 (Dermal)	H312
Acute Tox. 4 (Inhalation:vapour)	H332
Skin Irrit. 2	H315
Eye Dam. 1	H318
Asp. Tox. 1	H304
Full text of hazard classes and H-s	statements : see section 16
No additional information availab <b>2.2. Label elements</b> <b>Labelling according to Regulation</b> Hazard pictograms (CLP)	n (EC) No. 1272/2008 [CLP]
Signal word (CLP)	Danger
Hazardous ingredients	Xylenes (o-, m-, p- isomers), Silanetriol, methyl-, triacetate
Hazard statements (CLP)	H226 - Flammable liquid and vapour
	H304 - May be fatal if swallowed and enters airways
	H312+H332 - Harmful in contact with skin or if inhaled
20/12/2015	

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

	H315 - Causes skin irritation
	H318 - Causes serious eye damage
Precautionary statements (CLP)	<sup>2</sup> P210 - Keep away from heat, hot surfaces, sparks, open flames and
	other ignition sources. No smoking
	P233 - Keep container tightly closed
	P240 - Ground/bond container and receiving equipment
	P241 - Use explosion-proof electrical, ventilating, and lighting
	equipment
	P261 - Avoid breathing vapors, mist, spray
	P264 - Wash hands, forearms, and other exposed areas thoroughly
	after handling
	P271 - Use only outdoors or in a well-ventilated area
	P280 - Wear protective gloves, protective clothing, eye protection,
	and face protection
	P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or
	doctor
	P302+P352 - IF ON SKIN: Wash with plenty of water
	P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all
	contaminated clothing. Rinse skin with water/shower
	P304+P340 - IF INHALED: Remove person to fresh air and keep
	comfortable for breathing
	P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several
	minutes. Remove contact lenses, if present and easy to do.
	Continue rinsing
	P310 - Immediately call a POISON CENTER or doctor
	P312 - Call a POISON CENTER or doctor if you feel unwell
	P321 - Specific treatment (see section 4 on this SDS)
	P331 - Do NOT induce vomiting
	P332+P313 - If skin irritation occurs: Get medical advice/attention
	P362+P364 - Take off contaminated clothing and wash it before
	reuse
	P370+P378 - In case of fire: Use appropriate media to extinguish
	P403+P235 - Store in a well-ventilated place. Keep cool
	P405 - Store locked up
	P501 - Dispose of contents/container in accordance with
	local/national regulations
2.3. Other Hazards	

Other hazards not contributing to the classification

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

## **SECTION 3: Composition/information on ingredients**

#### 3.1. Substance

#### Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Xylenes (o-, m-, p- isomers)	(CAS No) 1330-20-7 (EC no) 215-535-7 (EC index no) 601-022-00-9	65 - 70	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Asp. Tox. 1, H304

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Silanetriol, methyl-, triacetate	(CAS No) 4253-34-3 (EC no) 224-221-9	< 5	Acute Tox. 4 (Oral), H302 Skin Corr. 1C, H314 Eye Dam. 1, H318

Full text of H-statements: see section 16

## **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

First-aid measures general	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	If inhaled, remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor/physician if you feel unwell.
First-aid measures after skin contact	Remove contaminated clothing. Rinse immediately with plenty of water (for at least 15 minutes). Obtain medical attention if irritation develops or persists. Wash contaminated clothing before reuse.
First-aid measures after eye contact	Rinse cautiously with water for at least 60 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.
First-aid measures after ingestion	Seek medical attention if a large amount is swallowed. Rinse mouth. Do NOT induce vomiting.
4.2. Most important symptoms of	and effects, both acute and delayed
Symptoms/injuries	Harmful in contact with skin. Harmful if inhaled. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness and dizziness.
Symptoms/injuries after inhalation	Harmful if inhaled.
Symptoms/injuries after skin contact	Harmful in contact with skin. Causes skin irritation.
Symptoms/injuries after eye contact	Causes serious eye damage.
Symptoms/injuries after ingestion	May be fatal if swallowed and enters airways.
4.3. Indication of any immediat	e medical attention and special treatment needed

If medical advice is needed, have product container or label at hand.

## **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing Media

Suitable extinguishing media	: Water spray or fog, dry chemical powder, alcohol-resistant foam,
	carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use a heavy water stream. Use of heavy stream of water may spread fire. Application of water stream to hot product may cause frothing and increase fire intensity.
5.2. Special Hazards Arising Fro	om the Substance or Mixture
Fire hazard	Flammable liquid and vapour.
Explosion hazard	May form flammable/explosive vapour-air mixture.
Reactivity	Hazardous reactions will not occur under normal conditions.
5.3. Advice for firefighters	
Precautionary measures fire	Exercise caution when fighting any chemical fire.
Firefighting instructions	Use water spray or fog for cooling exposed containers. Avoid release to the environment.
Protection during firefighting	Do not enter fire area without proper protective equipment, including respiratory protection.
30/12/2015	EN (English) 3/12

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

## SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

0.1. Tersonal precaditoris, profe	cive equipment and emergency procedures
General measures	Keep away from heat/sparks/open flames/hot surfaces. No smoking. Use special care to avoid static electric charges. Do not get in eyes,
	on skin, or on clothing. Do not breathe gas/vapour/aerosol.
6.1.1.For non-emergency person	nel
Protective equipment	Use appropriate personal protection equipment (PPE).
Emergency procedures	Evacuate unnecessary personnel.
6.1.2. For emergency responders	
Protective equipment	Equip cleanup crew with proper protection.
Emergency procedures	Ventilate area.
6.2. Environmental precautions	
Prevent entry to sewers and public v	vaters. Notify authorities if liquid enters sewers or public waters.
6.3. Methods and material for c	ontainment and cleaning up
For containment	Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up	Absorb and/or contain spill with inert material, then place in suitable container. Do not take up in combustible material such as: saw dust or cellulosic material. Use only non-sparking tools.

#### 6.4. Reference to other sections

Improves the adhesion of addition-cured systems to various substrates. For professional use only.

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Additional hazards when processed	Handle empty containers with care because residual vapours are flammable.
Precautions for safe handling	Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Provide good ventilation in process area to prevent formation of vapour. Take precautionary measures against static discharge. Use only non-sparking tools.
Hygiene measures	Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.
7.2. Conditions for safe storage, i	ncluding any incompatibilities
Technical measures	Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof electrical, lighting, ventilating equipment.
Storage conditions	Keep in fireproof place. Keep container tightly closed. Store in a dry cool and well-ventilated place.
Incompatible products	Strong bases. Strong acids. Strong oxidizers.
Incompatible products	Sources of ignition. Direct sunlight. Heat sources.
<b>7.3.</b> Specific end use(s) For professional use only.	

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Xylenes (o-, m-, p- isomers) (1330-20-7)		
EU	IOELV TWA (mg/m³)	221 mg/m³ (pure)
EU	IOELV TWA (ppm)	50 ppm (pure)

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

Xylenes (o-, m-, p-	isomers) (1330-20-7)	
EU	IOELV STEL (mg/m³)	442 mg/m³ (pure)
EU	IOELV STEL (ppm)	100 ppm (pure)
Austria	MAK (mg/m³)	221 mg/m³ (all isomers)
Austria	MAK (ppm)	50 ppm (all isomers)
Austria	MAK Short time value (mg/m³)	442 mg/m³ (all isomers)
Austria	MAK Short time value (ppm)	100 ppm (all isomers)
Belgium	Limit value (mg/m³)	221 mg/m³
Belgium	Limit value (ppm)	50 ppm
Belgium	Short time value (mg/m³)	442 mg/m <sup>3</sup>
Belgium	Short time value (ppm)	100 ppm
Bulgaria	OEL TWA (mg/m³)	221,0 mg/m³ (pure)
Bulgaria	OEL TWA (ppm)	50 ppm (pure)
Bulgaria	OEL STEL (mg/m³)	442 mg/m³ (pure)
Bulgaria	OEL STEL (ppm)	100 ppm (pure)
Croatia	GVI (granična vrijednost izloženosti)	
	(mg/m³)	221 mg/m³
Croatia	GVI (granična vrijednost izloženosti)	
	(ppm)	50 ppm
Croatia	KGVI (kratkotrajna granična vrijednost	
	izloženosti) (mg/m³)	442 mg/m <sup>3</sup>
Croatia	KGVI (kratkotrajna granična vrijednost	
	izloženosti) (ppm)	100 ppm
Cyprus	OEL TWA (mg/m³)	221 mg/m <sup>3</sup>
Cyprus	OEL TWA (ppm)	50 ppm
Cyprus	OEL STEL (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
Cyprus	OEL STEL (ppm)	100 ppm
France	VLE (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup> (restrictive limit)
France	VLE (ppm)	100 ppm (restrictive limit)
France	VME (mg/m <sup>3</sup> )	221 mg/m <sup>3</sup> (restrictive limit)
France	VME (ppm)	50 ppm (restrictive limit)
Germany	TRGS 900 Occupational exposure limit value (mg/m³)	440 mg/m³ (all isomers)
Germany	TRGS 900 Occupational exposure limit value (ppm)	100 ppm (all isomers)
Germany	TRGS 903 (BGW)	1,5 mg/l (Medium: whole blood - Time: end of shift - Parameter: Xylene (all isomers) 2000 mg/l (Medium: urine - Time: end of shift - Parameter: Methylhippuric(tolur- )acid (all isomers)
Gibraltar	OEL TWA (mg/m³)	221 mg/m³ (pure)
Gibraltar	OEL TWA (ppm)	50 ppm (pure)
Gibraltar	OEL STEL (mg/m³)	442 mg/m³ (pure)
Gibraltar	OEL STEL (ppm)	100 ppm (pure)
Greece	OEL TWA (mg/m³)	435 mg/m³
Greece	OEL TWA (ppm)	100 ppm
Greece	OEL STEL (mg/m³)	650 mg/m³
Greece	OEL STEL (ppm)	150 ppm

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

Xylenes (o-, m-, p- i	somers) (1330-20-7)	
USA ACGIH	ACGIH TWA (ppm)	100 ppm
USA ACGIH	ACGIH STEL (ppm)	150 ppm
Italy	OEL TWA (mg/m³)	221 mg/m <sup>3</sup> (pure)
Italy	OEL TWA (ppm)	50 ppm (pure)
Italy	OEL STEL (mg/m³)	442 mg/m <sup>3</sup> (pure)
Italy	OEL STEL (ppm)	100 ppm (pure)
Latvia	OEL TWA (mg/m³)	221 mg/m³
Latvia	OEL TWA (ppm)	50 ppm
Spain	VLA-ED (mg/m³)	221 mg/m³ (indicative limit value)
Spain	VLA-ED (ppm)	50 ppm (indicative limit value)
Spain	VLA-EC (mg/m³)	442 mg/m <sup>3</sup>
Spain	VLA-EC (ppm)	100 ppm
Switzerland	VLE (mg/m³)	870 mg/m <sup>3</sup>
Switzerland	VLE (ppm)	200 ppm
Switzerland	VME (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
Switzerland	VME (ppm)	100 ppm
Netherlands	Grenswaarde TGG 8H (mg/m <sup>3</sup> )	210 mg/m <sup>3</sup>
Netherlands	Grenswaarde TGG 15MIN (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
United Kingdom	WEL TWA (mg/m³)	220 mg/m <sup>3</sup>
United Kingdom	WEL TWA (ppm)	50 ppm
United Kingdom	WEL STEL (mg/m <sup>3</sup> )	441 mg/m <sup>3</sup>
United Kingdom	WEL STEL (ppm)	100 ppm
Czech Republic	Expoziční limity (PEL) (mg/m <sup>3</sup> )	200 mg/m <sup>3</sup>
Denmark	Grænseværdie (langvarig) (mg/m <sup>3</sup> )	109 mg/m <sup>3</sup>
Denmark	Grænseværdie (langvarig) (mg/m)	25 ppm
Estonia	OEL TWA (mg/m³)	221 mg/m <sup>3</sup>
Estonia	OEL TWA (ppm)	50 ppm
Estonia	OEL STEL (mg/m³)	442 mg/m <sup>3</sup>
Estonia	OEL STEL (ppm)	100 ppm
Finland	HTP-arvo (8h) (mg/m <sup>3</sup> )	220 mg/m <sup>3</sup>
Finland	HTP-arvo (8h) (ppm)	50 ppm
Finland	HTP-arvo (15 min)	440 mg/m <sup>3</sup>
Finland	HTP-arvo (15 min) (ppm)	100 ppm
Hungary	AK-érték	221 mg/m <sup>3</sup>
Hungary	CK-érték	442 mg/m <sup>3</sup>
Ireland	OEL (8 hours ref) (mg/m <sup>3</sup> )	221 mg/m <sup>3</sup>
Ireland	OEL (8 hours ref) (ppm)	50 ppm
Ireland	OEL (15 min ref) (mg/m3)	442 mg/m <sup>3</sup>
Ireland	OEL (15 min ref) (ppm)	100 ppm
Lithuania	IPRV (mg/m³)	200 mg/m <sup>3</sup>
Lithuania	IPRV (ppm)	50 ppm
Lithuania	TPRV (mg/m <sup>3</sup> )	450 mg/m <sup>3</sup>
Lithuania	TPRV (ppm)	100 ppm
Luxembourg	OEL TWA (mg/m³)	221 mg/m <sup>3</sup>
Luxembourg	OEL TWA (mg/m)	50 ppm
Luxembourg	OEL STEL (mg/m³)	442 mg/m <sup>3</sup>
Luxembourg	OEL STEL (mg/m ) OEL STEL (ppm)	100 ppm
30/12/2015	EN (English)	6/12

EN (English)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

Xylenes (o-, m-, p- isomers) (1330-20-7)		
Malta	OEL TWA (mg/m³)	221 mg/m³ (pure)
Malta	OEL TWA (ppm)	50 ppm (pure)
Malta	OEL STEL (mg/m³)	442 mg/m³ (pure)
Malta	OEL STEL (ppm)	100 ppm (pure)
Norway	Grenseverdier (AN) (mg/m <sup>3</sup> )	108 mg/m <sup>3</sup>
Norway	Grenseverdier (AN) (ppm)	25 ppm
Norway	Grenseverdier (Korttidsverdi) (mg/m3)	135 mg/m³
Norway	Grenseverdier (Korttidsverdi) (ppm)	37,5 ppm
Poland	NDS (mg/m³)	100 mg/m³
Romania	OEL TWA (mg/m³)	221 mg/m³
Romania	OEL TWA (ppm)	50 ppm
Romania	OEL STEL (mg/m³)	442 mg/m <sup>3</sup>
Romania	OEL STEL (ppm)	100 ppm
Slovakia	NPHV (priemerná) (mg/m³)	221 mg/m³
Slovakia	NPHV (priemerná) (ppm)	50 ppm
Slovakia	NPHV (Hraničná) (mg/m³)	442 mg/m <sup>3</sup>
Slovenia	OEL TWA (mg/m³)	221 mg/m³
Slovenia	OEL TWA (ppm)	50 ppm
Slovenia	OEL STEL (mg/m³)	442 mg/m <sup>3</sup>
Slovenia	OEL STEL (ppm)	100 ppm
Sweden	nivågränsvärde (NVG) (mg/m³)	221 mg/m³
Sweden	nivågränsvärde (NVG) (ppm)	50 ppm
Sweden	kortidsvärde (KTV) (mg/m³)	442 mg/m <sup>3</sup>
Sweden	kortidsvärde (KTV) (ppm)	100 ppm
Portugal	OEL TWA (mg/m³)	221 mg/m³ (indicative limit value)
Portugal	OEL TWA (ppm)	50 ppm (indicative limit value)
Portugal	OEL STEL (mg/m³)	442 mg/m³ (indicative limit value)
Portugal	OEL STEL (ppm)	100 ppm (indicative limit value)
Portugal	OEL chemical category (PT)	A4 - Not Classifiable as a Human Carcinogen,skin - potential for cutaneous exposure indicative limit value

#### 8.2. Exposure controls

 Appropriate engineering controls
 Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Gas detectors should be used when flammable gases/vapours may be released. Proper grounding procedures to avoid static electricity should be followed.

 Personal protective equipment
 Avoid all unnecessary exposure. Gloves. Protective clothing. Protective goggles. Face shield. Insufficient ventilation: wear respiratory protection.

 Materials for protective clothing
 Wear fire/flame resistant/retardant clothing.

 Wear chemically resistant protective gloves.
 Wear chemically resistant protective gloves.

Eye protection

Wear chemically resistant protective glo Chemical goggles or safety glasses.

EN (English)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010
Skin and body protection
Wear suitable protective clothing. Wash contaminated clothing

skin and body protection	before reuse.
Respiratory protection	Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed established
Environmental exposure controls Other information	Occupational Exposure Limits. Do not allow the product to be released into the environment. When using, do not eat, drink or smoke.

## **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

cui unu chemicui propeni	53
: Liquid	
: Translucent	
: Sweet/Solvent	
: No data availa	ble
: No data availa	ble
etate=1) : No data availa	ble
: No data availa	ble
: No data availa	ble
: No data availa	ble
: 26,7 °C (79,9°F)	
: No data availa	ble
: 0,92	
: No data availa	ble
er : No data availa	ble
: No data availa	ble
: No data availa	ble
: No data availa	ble
: No data availa	ble
: Not applicable	
65 - 70 %	
	er : Translucent : Sweet/Solvent : No data availa : 26,7 °C (79,9°F) : No data availa : No data availa

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Hazardous reactions will not occur under normal conditions.

#### 10.2. Chemical stability

Flammable liquid and vapour.

#### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

#### 10.4. Conditions to avoid

Ignition sources. Direct sunlight. Extremely high or low temperatures. Open flame. Sparks.

#### 10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizers.

#### 10.6. Hazardous decomposition products

Carbon oxides (CO, CO<sub>2</sub>). Silicon oxides. May release flammable gases. Hydrocarbons. Smoke. Oxides of tin.

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

## **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

Acute toxicity

Dermal: Harmful in contact with skin. Inhalation:vapour: Harmful if inhaled.

Xylenes (o-, m-, p- isomers) (1330-20-7)		
LD50 oral rat	> 5000 mg/kg	
LC50 inhalation rat (ppm)	6247 ppm/4h (species: Sprague-Dawley)	
Silanetriol, methyl-, triacetate (4253-34-3)		
LD50 oral rat	1437 - 1780 mg/kg	
Skin corrosion/irritation Serious eye damage/irritation Respiratory or skin sensitisation Germ cell mutagenicity Carcinogenicity Reproductive toxicity Specific target organ toxicity (single Specific target organ toxicity (repea		
exposure) Aspiration hazard	May be fatal if swallowed and enters airways.	

## SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general

Toxic to aquatic life.

Xylenes (o-, m-, p- isomers) (1330-20-7)	
3,3 mg/l	
3,82 mg/l (Exposure time: 48 h - Species: water flea)	
2,661 (2,661 - 4,093) mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])	

12.2. Persistence and degradability		
MED10-6605		
Persistence and degradability	Not established.	
12.3. Bioaccumulative potential		
MED10-6605		
Bioaccumulative potential	Not established.	
Xylenes (o-, m-, p- isomers) (1330-20-7)		
BCF fish 1	0,6 (0,6 - 15)	
Log Pow	2,77 - 3,15	
Silanetriol, methyl-, triacetate (4253-34-3)		
Log Pow	0,25 KowWin	
12.4. Mobility in soil		

No additional information available

#### 12.5. Results of PBT and vPvB assessment

No additional information available

#### 12.6. Other adverse effects

Other information

Avoid release to the environment.

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

## **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Waste disposal recommendations	Dispose of waste material in accordance with all local, regional, national, and international regulations.
Additional information	Handle empty containers with care because residual vapours are flammable.
Ecology - waste materials	Avoid release to the environment.

## **SECTION 14: Transport information**

In accordance with ADR / RID / IMDG / IATA / ADN

In accordance with ADR / RID / IMDC	J/IAIA/ADN
14.1. UN number	
UN-No. (ADR)	1307
14.2. UN proper shipping name	
Proper Shipping Name (ADR)	XYLENES (SOLUTION)
Transport document description	UN 1307 XYLENES (SOLUTION), 3, III, (D/E)
(ADR)	
14.3. Transport hazard class(es)	
Class (ADR)	3
Danger labels (ADR)	3
	3
14.4. Packing group	
14.5. Environmental hazards	
Other information	No supplementary information available.
14.6. Special precautions for user	
14.6.1. Overland transport	
Hazard identification number	30
(Kemler No.)	- F1
Classification code (ADR)	F1
Orange plates	30
	1207
	1307
Transport category (ADR)	3
Tunnel restriction code (ADR)	D/E
Limited quantities (ADR)	51
Excepted quantities (ADR)	E1
EAC code	3YE
14.6.2. Transport by sea	
MFAG-No	130
14.6.3. Air transport	

No additional information available

**14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no substance on the REACH candidate list Contains no REACH Annex XIV substances VOC content 65 - 70 %

#### 15.1.2. National regulations

No additional information available

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## **SECTION 16: Other information**

Indication of changes:

Section	Section Header	Change	Date Changed
1.3	Details of the supplier of the safety data sheet	Modified	30/12/2015
2	Hazards identification	Added Acute Tox. 4 (Inhalation:vapour) H332. Removed DSD/DPD information.	30/12/2015
3	Composition/information on ingredients	Changed component classifications. Removed not classified components and components below cutoffs. Removed DSD/DPD information.	30/12/2015
5, 6, 7, 10	Minor wording changes to whole sections	Modified	30/12/2015
14	Transport information	Changed to UN1307	30/12/2015
15.1.1	EU-Regulations	Modified	30/12/2015

Revision date Data sources 30/12/2015

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

Full text of H- and EUH-statements:

Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Muta. 2	Germ cell mutagenicity, Category 2
Repr. 1B	Reproductive toxicity, Category 1B
Skin Corr. 1C	Skin corrosion/irritation, Category 1C
Skin Irrit. 2	Skin corrosion/irritation, Category 2

#### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

Skin Sens. 1	Sensitisation — Skin, Category 1
STOT SE 1	Specific target organ toxicity — single exposure, Category
	1
H226	Flammable liquid and vapour
H301	Toxic if swallowed
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H341	Suspected of causing genetic defects
H360	May damage fertility or the unborn child
H370	Causes damage to organs
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

Nusil EU GHS SDS

We believe that the information contained herein is current as of the date of this Safety Data Sheet, and is offered in good faith. Since the use of this information and of these opinions and the conditions of the use of the product are not within the control of NuSil Technology, it is the user's obligation to determine the conditions of safe use of the product.



# Silicone Sales & Services UK - Ireland - Benelux

© 2020 - Polymer Systems Technology Limited™ Unit 2. Network 4. Cressex Business Park, Lincoln Road, High Wycombe, Bucks. HP12 3RF

## tel: +44 (0) 1494 446610

## web: https://www.silicone-polymers.com

## email: sales@silicone-polymers.co.uk

