
PLY-7560

Vinyl Endblocked Phenyl Copolymer Series

Product Profile

Description



- A series of clear, 5.5 mole % diphenylsiloxanes endblocked with reactive vinyl groups
- Available in standard viscosities of 500 cP (PLY1), 1,000 cP (PLY2), 10,000 cP (PLY3), 50,000 cP (PLY4) and 100,000 cP (PLY5) and others viscosities upon request

NUSII SILICONE TECHNOLOGY

Creative Partners in a Material World

NuSil Technology

1050 Cindy Lane • Carpinteria, CA 93013 805/684-8780 • 805/566-9905 Fax www.nusil.com

An ISO 9001 Certified Company

Applications

• For curing with crosslinkers and catalysts to form adhesives, sealant, rubbers and gels due to their reactive nature

ypical Properties	Result		Metric Conv.	ASTM	NT-TM
Appearance	Translucent		-	D2090	002
Specific Gravity	1.01		-	D792	003
Volatility	1%		-	D792	004
Refractive Index	1.43		-	D1747, D1218	018
Flash Point	600°F		-	-	-
	PLY1-7560	PLY2-7560	PLY3-7560	PLY4-7560	PLY5-7560
Molecular Weight*	14,000	26,000	60,000	115,000	129,000

*Theoretical calculation

Warnings About Product Safety

NuSil Technology believes that the information and data contained herein are accurate and reliable. However, the user is responsible to determine the material's suitability and safety of use. NuSil Technology cannot know each application's specific requirements and hereby notifies the user that it has not tested or determined this material's suitability or safety for use in any application. The user is responsible to adequately test and determine the safety and suitability for their application and NuSil Technology makes no warranty concerning fitness for any use or purpose. NuSil Technology has completed no testing to establish safety of use in any medical application.

NuSil Technology has tested this material only to determine if the product meets the applicable specifications. (Please contact NuSil Technology for assistance and recommendations when establishing specifications.) When considering the use of NuSil Technology products in a particular application, review the latest Material Safety Data Sheet and contact NuSil Technology with any questions about product safety information.

Do not use any chemical in a food, drug, cosmetic, or medical application or process until having determined the safety and legality of the use. The user is responsible to meet the requirements of the U.S. Food and Drug Administration (FDA)

Packaging

1 Pint (455 g)

Warranty

6 Months

1 Gallon (3.64 kg)

5 Gallon (18.2 kg)

and any other regulatory agencies. Before handling any other materials mentioned in the text, obtain available product safety information and take the necessary steps to ensure safety of use.

Specifications

Do not use the typical properties shown in this technical profile as a basis for preparing specifications. Please contact NuSil Technology for assistance and recommendations in establishing particular specifications.

Patent Warning

NuSil Technology disclaims any expressed or implied warranty against the infringement of any patent. NuSil Technology does not warrant the use or sale of the products described herein will not infringe the claims of any United States' or other country's patents covering the product itself, its use in combination with other products or its use in the operation of any process.

Warranty Information

NuSil Technology's warranty period is 6 months from the date of shipment when stored below 40°C in original unopened containers. Unless NuSil Technology provides a specific written warranty of fitness for a particular use, NuSil Technology's sole warranty is that the product will meet NuSil Technology's then current specification. NuSil Technology specifically disclaims any other expressed or implied warranty, including warranties of merchantability and fitness for use. The exclusive remedy and NuSil Technology's sole liability for breach of warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted. NuSil Technology expressly disclaims any liability for incidental or consequential damages.



Silicone Sales & Services UK - Ireland - Benelux

© 2023 - Polymer Systems Technology Limited™ Unit 2. Network 4. Cressex Business Park, Lincoln Road, High Wycombe, Bucks. HP12 3RF

tel: +44 (0) 1494 446610

web: https://www.silicone-polymers.com

email: sales@silicone-polymers.co.uk

