Version: 3.0

A avantor

NuSil

1.1. Product Identifier

Product form Product Name Synonyms Mixture R-1008-2 Silicone Coating

1.2. Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

1.2.1. Relevant Identified Uses Use of the Substance/Mixture

For professional use only.

1.2.2. Uses Advised Against

No additional information available

1.3. Details of the Supplier of the Safety Data Sheet

NuSil Technology Europe 1198 Avenue Maurice Donat Le Natura Bt. 2 06250 Mougins France +33 4 92 96 93 31 ehs@nusil.com www.nusil.com

1.4. Emergency Telephone Number

Emergency Number

: 800-424-9300 CHEMTREC (in US); +1 703-527-3887 CHEMTREC (International and Maritime) +(44)-870-8200418 +(353)-19014670

SECTION 2: Hazards Identification

2.1. Classification of the Substance or Mixture

Classification According to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 3 H226 Skin Irrit. 2 H315 Eye Irrit. 2 H319 Skin Sens. 1 H317 STOT SE 3 H335 STOT RE 2 H373 Asp. Tox. 1 H304 Full text of hazard classes and H-statements : see section 16

2.2. Label Elements

Labelling According to Regulation (EC) No. 1272/2008 [CLP]

Hazard Pictograms (CLP)

Signal Word (CLP)

GHS02

GHS07

CHSOR

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 2-Butanone, O,O',O"-(methylsilylidyne)trioxime; Dibutyltin Hazardous Ingredients dilaurate; Reaction mass of ethylbenzene and xylene Hazard Statements (CLP) H226 - Flammable liquid and vapour. H304 - May be fatal if swallowed and enters airways. H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation. H335 - May cause respiratory irritation. H373 - May cause damage to organs through prolonged or repeated exposure. Precautionary Statements (CLP) P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P240 - Ground and bond container and receiving equipment. P241 - Use explosion-proof electrical, ventilating, and lighting equipment. P242 - Use non-sparking tools. P243 - Take action to prevent static discharges. P260 - Do not breathe vapours, mist, spray P264 - Wash hands, forearms and face thoroughly after handling P271 - Use only outdoors or in a well-ventilated area. P272 - Contaminated work clothing should not be allowed out of the workplace. P280 - Wear eye protection, protective clothing, protective aloves P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor P302+P352 - IF ON SKIN: Wash with plenty of water P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water . P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 - Call a POISON CENTRE or doctor if you feel unwell. P321 - Specific treatment (see Section 4 on this SDS) P331 - Do NOT induce vomitina. P332+P313 - If skin irritation occurs: Get medical advice/attention. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P362+P364 - Take off contaminated clothing and wash it before reuse. P370+P378 - In case of fire: Use water spray, fog, carbon dioxide, dry chemical powder, foam to extinguish. P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up. P501 - Dispose of contents/container to hazardous or special

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other Hazards

Other Hazards Not Contributing to the Classification

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

SECTION 3: Composition/Information on Ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| J.Z. MIXIULES | T | | |
|---|---|---------|--|
| Name | Product Identifier | % | Classification According to Regulation (EC) No. 1272/2008 [CLP] |
| Reaction mass of ethylbenzene and xylene | (CAS-No.) Not Applicable (REACH Registration No.) 01-2119539452-40-0053 (EC-No.) 905-588-0 | 10 - 30 | Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 |
| 2-Butanone, O,O',O''- (methylsilylidyne)trioxime | (CAS-No.) 22984-54-9 (EC-No.) 245-366-4 | < 15 | Eye Irrit. 2, H319 Skin Sens. 1B, H317 STOT RE 2, H373 |
| DibutyItin dilaurate | (CAS-No.) 77-58-7 (EC-No.) 201-039-8 (EC Index-No.) 050-030-00-3 | < 0,3 | Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Muta. 2, H341 Repr. 1B, H360 STOT SE 1, H370 STOT RE 1, H372 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 |

Full text of H-statements: see section 16

SECTION 4: First Aid Measures

4.1. Description of First-aid Measures

| First-Aid Measures General | Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). |
|--|---|
| First-Aid Measures After Inhalation | If inhaled, remove to fresh air and keep at rest in a position comfortable for breathing. When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists. |
| First-Aid Measures After Skin Contact | Immediately remove contaminated clothing. Obtain medical attention if irritation/rash develops or persists. Immediately drench affected area with water for at least 15 minutes. |

Safety Data Sheet

| According to Regulation (EC) No. 1907/2006 (REACH) with its ar | nendment Regulation (EU) 2015/830 |
|--|--|
| First-Aid Measures After Eye Contact | Immediately rinse with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| | Obtain medical attention if pain, blinking or redness persist. |
| First-Aid Measures After | Do NOT induce vomiting. Rinse mouth. Immediately call a |
| Ingestion | POISON CENTER or doctor/physician. |
| • | ns and Effects Both Acute and Delayed |
| Symptoms/Effects | Causes serious eye irritation. Causes skin irritation. May cause respiratory irritation. Skin sensitisation. May be fatal if swallowed and enters airways. May cause damage to organs through prolonged or repeated exposure. |
| Symptoms/Effects After Inhalation | Irritation of the respiratory tract and the other mucous membranes. |
| Symptoms/Effects After Skin Contact | Redness, pain, swelling, itching, burning, dryness, and dermatitis. May cause an allergic skin reaction. |
| Symptoms/Effects After Eye Contact | Contact causes severe irritation with redness and swelling of the conjunctiva. |
| Symptoms/Effects After Ingestion | Aspiration into the lungs can occur during ingestion or vomiting and may cause lung injury. |
| Chronic Symptoms | May cause damage to organs through prolonged or repeated exposure. |
| | |

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If medical advice is needed, have product container or label at hand. If exposed or concerned, get medical advice and attention.

SECTION 5: Firefighting Measures

5.1. Extinguishing Media

| Suitable Extinguishing Media | Water spray, fog, carbon dioxide, dry chemical powder, alcohol foam, polymer foam. |
|--|---|
| Unsuitable Extinguishing Media | Do not use a heavy water stream. A heavy water stream may spread burning liquid. Application of water stream to hot product may cause frothing and increase fire intensity. |
| 5.2. Special Hazards Arising F | rom the Substance or Mixture |
| Fire Hazard | Flammable liquid and vapour. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours. |
| Explosion Hazard | May form flammable/explosive vapour-air mixture. |
| Reactivity | Reacts violently with strong oxidisers. Increased risk of fire or explosion. |
| Hazardous Decomposition Products in Case of Fire | Silicon oxides. Carbon oxides (CO, CO ₂). Hydrocarbons. Smoke. Oxides of tin. |
| 5.3. Advice for Firefighters | |
| Precautionary Measures Fire Firefighting Instructions | Exercise caution when fighting any chemical fire. Do not breathe fumes from fires or vapours from decomposition. Use water spray or fog for cooling exposed containers. Avoid release to the environment. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion. |
| Protection During Firefighting | Do not enter fire area without proper protective equipment, including respiratory protection. |

Safety Data Sheet According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 6: Accidental Release Measures

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

| General Measures | Avoid breathing (vapor, mist, spray). Avoid all contact with skin, eyes, or clothing. Use special care to avoid static electric charges. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. |
|---------------------------------|--|
| 6.1.1. For Non-Emergency Person | nel |
| Protective Equipment | Use appropriate personal protective equipment (PPE). |
| Emergency Procedures | Evacuate unnecessary personnel. Stop leak if safe to do so. |
| 6.1.2. For Emergency Responders | i i i i i i i i i i i i i i i i i i i |
| Protective Equipment | Equip cleanup crew with proper protection. |
| Emergency Procedures | Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area. Eliminate ignition sources. |
| 6.2. Environmental Precaution | ns |

Environmental Precautions 0.Z.

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Methods and Materials for Containment and Cleaning Up 63

| v.v. memous and materia | |
|----------------------------|---|
| For Containment | Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions. |
| Methods For Cleaning Up | Clean up spills immediately and dispose of waste safely. Absorb and/or contain spill with inert material. Do not take up in combustible material such as: saw dust or cellulosic material. Transfer spilled material to a suitable container for disposal. Use only non-sparking tools. Contact competent authorities after a spill. |
| 6.4. Reference to Other Se | ections |

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: Handling And Storage

Precautions for Safe Handling 7.1.

| Additional Hazards When Processed | Handle empty containers with care because residual vapours are flammable. When heated, material emits irritating fumes. Any proposed use of this product in elevated-temperature processes should be thoroughly evaluated to assure that safe operating conditions are established and maintained. |
|--------------------------------------|--|
| Precautions for Safe Handling | Avoid breathing vapors, mist, spray. Avoid contact with eyes, skin and clothing. Take precautionary measures against static discharge. Use only non-sparking tools. Keep away from heat, sparks, open flames, hot surfaces. – No smoking. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. |
| Hygiene Measures | Handle in accordance with good industrial hygiene and safety procedures. |

Safety Data Sheet According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

7.2 Conditions for Safe Storage Including Any Incompatibilities

| 7.2. Conditions for sale storage, including Any incompatibilities | | | |
|---|---|--|--|
| Technical Measures | Comply with applicable regulations. Take action to prevent static discharges. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment. | | |
| Storage Conditions | Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area. Store in a well- ventilated place. Keep container tightly closed. Keep in fireproof place. | | |
| Incompatible Materials | Strong acids, strong bases, strong oxidizers. | | |
| 7.3. Specific End Use(S) For professional use only. | | | |

SECTION 8: Exposure Controls/Personal Protection

8.1. Control Parameters

| Xylenes (o-, m-, p- isomers) | | | |
|------------------------------|--|---|--|
| EU | IOELV TWA (mg/m³) | 221 mg/m ³ (pure) | |
| EU | IOELV TWA (ppm) | 50 ppm (pure) | |
| EU | IOELV STEL (mg/m³) | 442 mg/m ³ (pure) | |
| EU | IOELV STEL (ppm) | 100 ppm (pure) | |
| EU | Notes | Possibility of significant uptake through the skin (pure) | |
| Austria | MAK (mg/m³) | 221 mg/m ³ (all isomers) | |
| Austria | MAK (ppm) | 50 ppm (all isomers) | |
| Austria | MAK Short time value (mg/m³) | 442 mg/m ³ | |
| Austria | MAK Short time value (ppm) | 100 ppm | |
| Belgium | Limit value (mg/m³) | 221 mg/m ³ | |
| Belgium | Limit value (ppm) | 50 ppm | |
| Belgium | Short time value (mg/m³) | 442 mg/m ³ | |
| Belgium | Short time value (ppm) | 100 ppm | |
| Belgium | OEL chemical category (BE) | Skin, Skin notation pure | |
| Bulgaria | OEL TWA (mg/m³) | 221 mg/m³ (pure) | |
| Bulgaria | OEL TWA (ppm) | 50 ppm (pure) | |
| Bulgaria | OEL STEL (mg/m³) | 442 mg/m³ (pure) | |
| Bulgaria | OEL STEL (ppm) | 100 ppm (pure) | |
| Croatia | GVI (granična vrijednost izloženosti) (mg/m³) | 221 mg/m³ | |
| Croatia | GVI (granična vrijednost izloženosti) (ppm) | 50 ppm | |
| Croatia | KGVI (kratkotrajna granična vrijednost izloženosti) (mg/m³) | 442 mg/m ³ | |
| Croatia | KGVI (kratkotrajna granična vrijednost izloženosti) (ppm) | 100 ppm | |
| Croatia | OEL chemical category (HR) | Skin notation | |
| Croatia | Croatia - BLV | 1,5 mg/l Parameter: Xylene - | |

| According to Regulation (EC) No. | 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 | 1 |
|----------------------------------|---|---|
| | | Medium: blood - Sampling time: at the end of the work shift (alcohol before exposure to Xylene raises occurrence) 1,5 g/g creatinine Parameter: Methylhippuric acid - Medium: urine - Sampling time: at the end of the work shift (calculated on the average Creatinine value of 1.2 g/L urine) |
| Cyprus | OEL TWA (mg/m³) | 221 mg/m ³ |
| Cyprus | OEL TWA (ppm) | 50 ppm |
| Cyprus | OEL STEL (mg/m ³) | 442 mg/m ³ |
| Cyprus | OEL STEL (ppm) | 100 ppm |
| Cyprus | OEL chemical category (CY) | Skin-potential for cutaneous absorption |
| Czech Republic | Expoziční limity (PEL) (mg/m³) | 200 mg/m ³ |
| Czech Republic | OEL chemical category (CZ) | Potential for cutaneous absorption |
| Czech Republic | Czech Republic - BLV | 820 µmol/mmol Creatinine Parameter: Methylhippuric acid - Medium: urine - Sampling time: end of shift 1400 mg/g creatinine Parameter: Methylhippuric acid - Medium: urine - Sampling time: end of shift |
| Denmark | Grænseværdie (langvarig) (mg/m³) | 109 mg/m ³ (Xylene, all isomers) |
| Denmark | Grænseværdie (langvarig) (ppm) | 25 ppm (Xylene, all isomers) |
| Estonia | OEL TWA (mg/m³) | 200 mg/m ³ |
| Estonia | OEL TWA (ppm) | 50 ppm |
| Estonia | OEL STEL (mg/m³) | 450 mg/m ³ |
| Estonia | OEL STEL (ppm) | 100 ppm |
| Estonia | OEL chemical category (ET) | Skin notation |
| Finland | HTP-arvo (8h) (mg/m³) | 220 mg/m³ |
| Finland | HTP-arvo (8h) (ppm) | 50 ppm |
| Finland | HTP-arvo (15 min) | 440 mg/m ³ |
| Finland | HTP-arvo (15 min) (ppm) | 100 ppm |
| Finland | OEL chemical category (FI) | Potential for cutaneous absorption |
| Finland | Finland - BLV | Parameter: Methylhippuric acid - Medium: urine - Sampling time: after the shift |
| France | VLE (mg/m³) | 442 mg/m ³ (restrictive limit) |
| France | VLE (ppm) | 100 ppm (restrictive limit) |
| France | VME (mg/m³) | 221 mg/m³ (restrictive limit) |
| France | VME (ppm) | 50 ppm (restrictive limit) |
| France | OEL chemical category (FR) | Risk of cutaneous absorption |
| France | France - BLV | 1500 mg/g creatinine Parameter: Methylhippuric acid - Medium: urine - Sampling time: end of shift |

| Germany | Occupational exposure limit value (mg/m³) | 440 mg/m ³ (all isomers) |
|------------|---|--|
| Germany | Occupational exposure limit value (ppm) | 100 ppm (all isomers) |
| Germany | TRGS 903 Biological limit value | 2000 mg/l Parameter: Methylhippuric(tolur-)acid (all isomers) - Medium: urine - Sampling time: end of shift (all isomers) |
| Germany | Chemical category | Skin notation all isomers |
| Gibraltar | Eight hours mg/m3 | 221 mg/m³ (pure) |
| Gibraltar | Eight hours ppm | 50 ppm (pure) |
| Gibraltar | Short-term mg/m3 | 442 mg/m³ (pure) |
| Gibraltar | Short-term ppm | 100 ppm (pure) |
| Gibraltar | OEL chemical category (GI) | Skin notation pure |
| Greece | OEL TWA (mg/m ³) | 435 mg/m ³ |
| Greece | OEL TWA (ppm) | 100 ppm |
| Greece | OEL STEL (mg/m ³) | 650 mg/m ³ |
| Greece | OEL STEL (ppm) | 150 ppm |
| Greece | OEL chemical category (GR) | skin - potential for cutaneous absorption |
| Hungary | AK-érték | 221 mg/m ³ |
| Hungary | CK-érték | 442 mg/m ³ |
| Hungary | OEL chemical category (HU) | Potential for cutaneous absorption |
| Ireland | OEL (8 hours ref) (mg/m ³) | 221 mg/m ³ |
| Ireland | OEL (8 hours ref) (ppm) | 50 ppm |
| Ireland | OEL (15 min ref) (mg/m3) | 442 mg/m ³ |
| Ireland | OEL (15 min ref) (ppm) | 100 ppm |
| Ireland | OEL chemical category (IE) | Potential for cutaneous absorption |
| Italy | OEL TWA (mg/m ³) | 221 mg/m ³ (pure) |
| Italy | OEL TWA (ppm) | 50 ppm (pure) |
| Italy | OEL STEL (mg/m ³) | 442 mg/m ³ (pure) |
| Italy | OEL STEL (ppm) | 100 ppm (pure) |
| Italy | OEL chemical category (IT) | skin - potential for cutaneous absorption pure |
| Latvia | OEL TWA (mg/m³) | 221 mg/m ³ |
| Latvia | OEL TWA (ppm) | 50 ppm |
| Latvia | OEL chemical category (LV) | skin - potential for cutaneous exposure |
| Lithuania | IPRV (mg/m³) | 221 mg/m ³ (mixed isomers, pure) |
| Lithuania | IPRV (ppm) | 50 ppm (mixed isomers, pure) |
| Lithuania | TPRV (mg/m ³) | 442 mg/m ³ (mixed isomers, pure) |
| Lithuania | TPRV (ppm) | 100 ppm (mixed isomers, pure) |
| Lithuania | OEL chemical category (LT) | Skin notation |
| Luxembourg | OEL TWA (mg/m ³) | 221 mg/m ³ |
| Luxembourg | OEL TWA (ppm) | 50 ppm |

| Luxembourg | OEL STEL (mg/m³) | 442 mg/m ³ |
|-------------|---|--|
| Luxembourg | OEL STEL (ppm) | 100 ppm |
| Luxembourg | OEL chemical category (LU) | Possibility of significant uptake through the skin |
| Malta | OEL TWA (mg/m³) | 221 mg/m³ (pure) |
| Malta | OEL TWA (ppm) | 50 ppm (pure) |
| Malta | OEL STEL (mg/m³) | 442 mg/m³ (pure) |
| Malta | OEL STEL (ppm) | 100 ppm (pure) |
| Malta | OEL chemical category (MT) | Possibility of significant uptake through the skin pure |
| Netherlands | Grenswaarde TGG 8H (mg/m³) | 210 mg/m ³ |
| Netherlands | Grenswaarde TGG 15MIN (mg/m³) | 442 mg/m ³ |
| Norway | Grenseverdier (AN) (mg/m ³) | 108 mg/m ³ |
| Norway | Grenseverdier (AN) (ppm) | 25 ppm |
| Norway | Grenseverdier (Korttidsverdi) (mg/m3) | 135 mg/m³ (value calculated) |
| Norway | Grenseverdier (Korttidsverdi) (ppm) | 37,5 ppm (value calculated) |
| Norway | OEL chemical category (NO) | Skin notation |
| Poland | NDS (mg/m³) | 100 mg/m ³ (mixture of isomers) |
| Poland | NDSCh (mg/m³) | 200 mg/m³ (mixture of isomers) |
| Portugal | OEL TWA (mg/m³) | 221 mg/m³ (indicative limit value) |
| Portugal | OEL TWA (ppm) | 50 ppm (indicative limit value) |
| Portugal | OEL STEL (mg/m³) | 442 mg/m³ (indicative limit value) |
| Portugal | OEL STEL (ppm) | 100 ppm (indicative limit value) |
| Portugal | OEL chemical category (PT) | A4 - Not Classifiable as a Human Carcinogen,skin - potential for cutaneous exposure indicative limit value |
| Romania | OEL TWA (mg/m³) | 221 mg/m ³ (pure) |
| Romania | OEL TWA (ppm) | 50 ppm (pure) |
| Romania | OEL STEL (mg/m³) | 442 mg/m ³ (pure) |
| Romania | OEL STEL (ppm) | 100 ppm (pure) |
| Romania | OEL chemical category (RO) | Skin notation pure |
| Romania | Romania - BLV | 3 g/l Parameter: Methylhippuric acid - Medium: urine - Sampling time: end of shift |
| Slovakia | NPHV (priemerná) (mg/m³) | 221 mg/m³ |
| Slovakia | NPHV (priemerná) (ppm) | 50 ppm |
| Slovakia | NPHV (Hraničná) (mg/m³) | 442 mg/m ³ |
| Slovakia | OEL chemical category (SK) | Potential for cutaneous absorption |
| Slovakia | Slovakia - BLV | 1,5 mg/l Parameter: Xylene - Medium: blood - Sampling time: end of exposure or work shift (all isomers) 2000 mg/l Parameter: Methylhippuric acid - Medium: urine - Sampling time: end of exposure or work shift |
| Slovenia | OEL TWA (mg/m³) | 221 mg/m ³ |

| | | EQ revenue | |
|------------------|--|--|--|
| Slovenia | OEL TWA (ppm) | 50 ppm | |
| Slovenia | OEL STEL (mg/m ³) | 442 mg/m ³ | |
| Slovenia | OEL STEL (ppm) | 100 ppm | |
| Slovenia | OEL chemical category (SI) | Potential for cutaneous absorption | |
| Spain | VLA-ED (mg/m ³) | 221 mg/m ³ (indicative limit value) | |
| Spain | VLA-ED (ppm) | 50 ppm (indicative limit value) | |
| Spain | VLA-EC (mg/m³) | 442 mg/m ³ | |
| Spain | VLA-EC (ppm) | 100 ppm | |
| Spain | OEL chemical category (ES) | skin - potential for cutaneous absorption | |
| Spain | Spain - BLV | 1 g/g creatinine Parameter: Methylhippuric acids - Medium: urine - Sampling time: end of shift | |
| Sweden | nivågränsvärde (NVG) (mg/m³) | 221 mg/m³ (Xylene) | |
| Sweden | nivågränsvärde (NVG) (ppm) | 50 ppm (Xylene) | |
| Sweden | kortidsvärde (KTV) (mg/m³) | 442 mg/m³ (Xylene) | |
| Sweden | kortidsvärde (KTV) (ppm) | 100 ppm (Xylene) | |
| Sweden | OEL chemical category (SE) | Skin notation | |
| Switzerland | KZGW (mg/m³) | 870 mg/m ³ | |
| Switzerland | KZGW (ppm) | 200 ppm | |
| Switzerland | MAK (mg/m³) | 435 mg/m ³ | |
| Switzerland | MAK (ppm) | 100 ppm | |
| Switzerland | OEL chemical category (CH) | Skin notation | |
| Switzerland | Switzerland - BLV | 2 g/l Parameter: Methylhippuric acid - Medium: urine - Sampling time: end of shift | |
| United Kingdom | WEL TWA (mg/m³) | 220 mg/m ³ | |
| United Kingdom | WEL TWA (ppm) | 50 ppm | |
| United Kingdom | WEL STEL (mg/m ³) | 441 mg/m ³ | |
| United Kingdom | WEL STEL (ppm) | 100 ppm | |
| United Kingdom | WEL chemical category | Potential for cutaneous absorption | |
| Tin organic comp | ounds | | |
| Austria | MAK (mg/m³) | 0,1 mg/m³ (except tri-n-Butyltin compounds-inhalable fraction) | |
| Austria | MAK Short time value (mg/m³) | 0,2 mg/m³ (except Tri-n-butyltin compounds-inhalable fraction) | |
| Austria | OEL chemical category (AT) | Skin notation except Tri-n-butyltin compounds | |
| Belgium | Limit value (mg/m³) | 0,1 mg/m ³ | |
| Belgium | Short time value (mg/m³) | 0,2 mg/m ³ | |
| Belgium | OEL chemical category (BE) | Skin | |
| Bulgaria | OEL TWA (mg/m ³) | 0,1 mg/m ³ | |
| Croatia | GVI (granična vrijednost izloženosti) (mg/m³) | 0,1 mg/m³ (except Cyhexatin) | |
| Croatia | KGVI (kratkotrajna granična vrijednost | 0,2 mg/m ³ (except Cyhexatin) | |
| 2.000 | | | |

Safety Data Sheet According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| | izloženosti) (mg/m³) | |
|----------------|---|--|
| Czech Republic | Expoziční limity (PEL) (mg/m ³) | 0,1 mg/m ³ |
| Czech Republic | OEL chemical category (CZ) | Potential for cutaneous absorption |
| Denmark | Grænseværdie (langvarig) (mg/m ³) | 0,1 mg/m ³ (except Tri-n-butyltin |
| | | compounds) |
| Estonia | OEL TWA (mg/m³) | 0,1 mg/m ³ |
| Estonia | OEL STEL (mg/m ³) | 0,2 mg/m ³ |
| Estonia | OEL chemical category (ET) | Skin notation |
| Finland | HTP-arvo (8h) (mg/m³) | 0,1 mg/m³ |
| Finland | HTP-arvo (15 min) | 0,3 mg/m ³ |
| Finland | OEL chemical category (FI) | Potential for cutaneous absorption |
| France | VLE (mg/m ³) | 0,2 mg/m ³ |
| France | VME (mg/m ³) | 0,1 mg/m ³ |
| Greece | OEL TWA (mg/m ³) | 0,1 mg/m ³ |
| Greece | OEL STEL (mg/m ³) | 0,2 mg/m ³ |
| Greece | OEL chemical category (GR) | skin - potential for cutaneous |
| | | absorption |
| Hungary | AK-érték | 0,1 mg/m ³ |
| Hungary | CK-érték | 0,4 mg/m ³ |
| Hungary | OEL chemical category (HU) | Potential for cutaneous absorption |
| Ireland | OEL (8 hours ref) (mg/m ³) | 0,1 mg/m ³ |
| Ireland | OEL (15 min ref) (mg/m3) | 0,2 mg/m ³ |
| Lithuania | IPRV (mg/m ³) | 0,1 mg/m ³ |
| Lithuania | TPRV (mg/m ³) | 0,2 mg/m ³ |
| Lithuania | OEL chemical category (LT) | Skin notation |
| Norway | Grenseverdier (AN) (mg/m ³) | 0,1 mg/m ³ |
| Norway | Grenseverdier (Korttidsverdi) (mg/m3) | 0,3 mg/m³ (value calculated) |
| Norway | OEL chemical category (NO) | Skin notation |
| Portugal | OEL TWA (mg/m³) | 0,1 mg/m ³ |
| Portugal | OEL STEL (mg/m³) | 0,2 mg/m ³ |
| Portugal | OEL chemical category (PT) | A4 - Not Classifiable as a Human |
| | | Carcinogen,skin - potential for |
| | | cutaneous exposure |
| Romania | OEL TWA (mg/m³) | 0,05 mg/m ³ |
| Romania | OEL STEL (mg/m³) | 0,15 mg/m ³ |
| Slovakia | NPHV (priemerná) (mg/m³) | 0,1 mg/m ³ |
| Slovakia | NPHV (Hraničná) (mg/m³) | 0,2 mg/m ³ |
| Slovakia | OEL chemical category (SK) | Potential for cutaneous absorption |
| Spain | VLA-ED (mg/m³) | 0,1 mg/m³ |
| Spain | VLA-EC (mg/m³) | 0,2 mg/m ³ |
| Spain | OEL chemical category (ES) | skin - potential for cutaneous |
| Swadan | | absorption |
| Sweden | nivågränsvärde (NVG) (mg/m ³) | 0,1 mg/m ³ (total dust) |
| Sweden | kortidsvärde (KTV) (mg/m ³) | 0,2 mg/m ³ (total dust) |
| Sweden | OEL chemical category (SE) | Skin notation |

EN (English)

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| Switzerland | KZGW (mg/m³) | 0,2 mg/m³ (inhalable dust) | |
|----------------|----------------------------|---|--|
| Switzerland | MAK (mg/m³) | 0,1 mg/m³ (inhalable dust) | |
| Switzerland | OEL chemical category (CH) | Skin notation | |
| United Kingdom | WEL TWA (mg/m³) | 0,1 mg/m³ (except Cyhexatin) | |
| United Kingdom | WEL STEL (mg/m³) | 0,2 mg/m³ (except Cyhexatin) | |
| United Kingdom | WEL chemical category | Potential for cutaneous absorption except Cyhexatin | |

Exposure Controle 0 7

| 8.2. Exposure Controls | |
|-------------------------------------|--|
| Appropriate Engineering Controls | Ensure all national/local regulations are observed. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Take precautionary measures against static discharges. Use explosion-proof equipment. Proper grounding procedures to avoid static electricity should be followed. Gas detectors should be used when flammable gases/vapours may be released. |
| Personal Protective Equipment | Protective clothing. Protective goggles. Gloves. Insufficient ventilation: wear respiratory protection. |
| Materials for Protective Clothing | Wear fire/flame resistant/retardant clothing. Chemically resistant materials and fabrics. |
| Hand Protection | Wear protective gloves. |
| Eye Protection | Chemical safety goggles. |
| Skin and Body Protection | Wear suitable protective clothing. |
| Respiratory Protection | If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection. |
| | |

Other Information

When using, do not eat, drink or smoke.

SECTION 9: Physical and Chemical Hazards

Information on Basic Physical and Chemical Properties 9.1.

| Physical State | Liquid |
|---------------------------|-------------------|
| Colour | Black |
| Odour | Solvent |
| Odour Threshold | No data available |
| рН | No data available |
| Evaporation Rate | No data available |
| Melting Point | No data available |
| Freezing Point | No data available |
| Boiling Point | 140 °C (284 °F) |
| Flash Point | 27 °C (81 °F) |
| Auto-Ignition Temperature | No data available |
| Decomposition Temperature | No data available |
| Flammability (Solid, Gas) | Not applicable |

Safety Data Sheet According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| Vapour Pressure Relative Vapour Density At 20 °C | No data available No data available |
|---|--|
| Relative Density | > 1 (water=1) |
| Solubility | No data available |
| Partition Coefficient n-Octanol/Water | No data available |
| Viscosity, Kinematic | No data available |
| Viscosity, Dynamic | No data available |
| Explosive Properties | No data available |
| Oxidising Properties | No data available |
| Explosive Limits | No data available |
| 9.2. Other Information | |
| VOC content 10 - | 30 % |

SECTION 10: Stability and Reactivity

10.1. Reactivity

Reacts violently with strong oxidisers. Increased risk of fire or explosion.

10.2. Chemical Stability

Flammable liquid and vapour. May form flammable or explosive vapour-air mixture.

10.3. Possibility Of Hazardous Reactions

Hazardous polymerization will not occur.

10.4. Conditions To Avoid

Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.

10.5. Incompatible Materials

Strong acids, strong bases, strong oxidizers.

10.6. Hazardous Decomposition Products

Thermal decomposition may produce: Silicon oxides. Carbon oxides (CO, CO₂). Hydrocarbons. Smoke. Oxides of tin.

SECTION 11: Toxicological Information

11.1. Information On Toxicological Effects

Acute Toxicity

Not classified (Based on available data, the classification criteria are not met)

| | , | |
|--|-----------------------|--|
| 2-Butanone, O,O',O''-(methylsilylidyne)trioxime (22984-54-9) | | |
| LD50 Oral Rat | 2463 mg/kg | |
| LD50 Dermal Rat | > 2000 mg/kg | |
| ATE CLP (oral) | 2463 mg/kg bodyweight | |
| Dibutyltin dilaurate (77-58-7) | | |
| LD50 Oral | 175 mg/kg | |
| LD50 Dermal Rat | > 2 g/kg | |
| Reaction mass of ethylbenzene and xyleneNot Applicable (REACH Registration No.) 01-2119539452-40-0053 | | |
| LD50 Oral Rat | 3523 mg/kg | |
| LC50 Inhalation Rat | 6700 ppm/4h | |
| ATE CLP (oral) | 3523 mg/kg bodyweight | |
| ATE CLP (dermal) | 1100 mg/kg bodyweight | |

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Reaction mass of ethylbenzene and xyleneNot Applicable (REACH Registration No.) 01-2119539452-40-0053 ATE CLP (gases) 6700 ppmv/4h ATE CLP (vapours) 11 mg/l/4h Skin Corrosion/Irritation Causes skin irritation. Eye Damage/Irritation Causes serious eve irritation. Respiratory or Skin Sensitization May cause an allergic skin reaction. Germ Cell Mutagenicity Not classified (Based on available data, the classification criteria are not met) Not classified (Based on available data, the classification Carcinogenicity criteria are not met) **Reproductive Toxicity** Not classified (Based on available data, the classification criteria are not met) May cause respiratory irritation. Specific Target Organ Toxicity (Single Exposure) Specific Target Organ Toxicity (Repeated May cause damage to organs through Exposure) prolonged or repeated exposure. Aspiration Hazard May be fatal if swallowed and enters airways.

SECTION 12: Ecological Information

12.1. Toxicity

| Ecology - General | Not classified. | | | |
|--|--|--|--|--|
| 2-Butanone, O,O',O''-(methylsilylidyne)trioxime (22984-54-9) | | | | |
| EC50 Daphnia 1 | 120 mg/l (Exposure time: 48h - Species: Daphnia magna) | | | |
| Dibutyltin dilaurate (77-58-7) | | | | |
| EC50 Daphnia 1 | 0,463 mg/l (Daphnia magna) | | | |
| 12.2. Persistence and Degrad | 12.2. Persistence and Degradability | | | |
| R-1008-2 | | | | |
| Persistence and Degradability | Not established. | | | |
| 12.3. Bioaccumulative Potential | | | | |
| R-1008-2 | | | | |
| Bioaccumulative potential | Not established. | | | |
| DibutyItin dilaurate (77-58-7) | | | | |
| Log Pow | 4,44 | | | |
| 12.4. Mobility in Soil | | | | |
| No additional information available | | | | |
| 12.5. Results of PBT and vPvB assessment | | | | |

No additional information available

12.6. Other Adverse Effects

Other Information

Avoid release to the environment.

SECTION 13: Disposal Considerations

13.1. Waste Treatment Methods

| Product/Packaging Disposal | Dispose of waste material in accordance with all local, |
|----------------------------|---|
| Recommendations | regional, national, and international regulations. |
| Additional Information | Handle empty containers with care because residual vapours are flammable. |

Safety Data Sheet According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Ecology - Waste Materials Avoid release to the environment.

SECTION 14: Transport Information

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

In accordance with ADR / RID / IMDG / IATA / ADN

| In accordance wit | n adr / Rid / Imdg , | / IATA / ADN | | |
|-------------------|----------------------|-------------------|-------------------|-------------------|
| ADR | IMDG | IATA | ADN | RID |
| 14.1. UN Numbe | r | | | |
| 1307 | 1307 | 1307 | 1307 | 1307 |
| 14.2. UN Proper S | Shipping Name | | | |
| XYLENES | XYLENES | XYLENES | XYLENES | XYLENES |
| (Solution) | (Solution) | (Solution) | (Solution) | (Solution) |
| 14.3. Transport H | azard Class(Es) | | | |
| 3 | 3 | 3 | 3 | 3 |
| | | | | |
| 14.4. Packing Gr | oup | | | |
| | | | | |
| 14.5. Environme | ntal Hazards | | | |
| Dangerous for | Dangerous for | Dangerous for | Dangerous for | Dangerous for |
| the environment : | the environment : | the environment : | the environment : | the environment : |
| No | No | No | No | No |
| | Marine pollutant : | | | |
| | No | | | |
| 146 Special Pro | cautions For Usor | | | |

14.6. Special Precautions For User

No additional information available

14.7. Transport in Bulk According to Annex II of MARPOL and The IBC Code Not applicable

SECTION 15: Regulatory Information

15.1. Safety, Health and Environmental Regulations/Legislation Specific for the Substance or Mixture

15.1.1. EU-Regulations

Contains no substance on the REACH candidate list Contains no REACH Annex XIV substances

15.1.2. National Regulations

No additional information available

15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out

SECTION 16: Other Information

Indication of Changes

| Section | Section Header | Change | Date Changed |
|---------|--|----------|--------------|
| 1 | Identification of the Substance/mixture and of the | Modified | 06/04/2020 |

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| | Company/Undertaking | | |
|---|---|----------|------------|
| 2 | Classification According to Regulation (EC) No. 1272/2008 [CLP] | Modified | 06/04/2020 |
| 3 | Composition/information on ingredients | Modified | 06/04/2020 |

Date of Preparation or Latest 06/04/2020 Revision Data Sources Information of

Information and data obtained and used in the authoring of this safety data sheet could come from database subscriptions, official government regulatory body websites, product/ingredient manufacturer or supplier specific information, and/or resources that include substance specific data and classifications according to GHS or their subsequent adoption of GHS. According to Regulation (EC) No. 1907/2006 (REACH) with its

Other Information

amendment Regulation (EU) 2015/830

Full Text of H- and EUH-statements:

| Acute Tox. 4 (Dermal) | Acute toxicity (dermal), Category 4 |
|-------------------------------------|---|
| Acute Tox. 4 (Inhalation:vapour) | Acute toxicity (inhalation:vapour) Category 4 |
| Aquatic Acute 1 | Hazardous to the aquatic environment — Acute Hazard, Category 1 |
| Aquatic Chronic 1 | Hazardous to the aquatic environment — Chronic Hazard, Category 1 |
| Asp. Tox. 1 | Aspiration hazard, Category 1 |
| Eye Dam. 1 | Serious eye damage/eye irritation, Category 1 |
| Eye Irrit. 2 | Serious eye damage/eye irritation, Category 2 |
| Flam. Liq. 3 | Flammable liquids, Category 3 |
| Muta. 2 | Germ cell mutagenicity, Category 2 |
| Repr. 1B | Reproductive toxicity, Category 1B |
| Skin Corr. 1C | Skin corrosion/irritation, Category 1C |
| Skin Irrit. 2 | Skin corrosion/irritation, Category 2 |
| Skin Sens. 1 | Skin sensitisation, Category 1 |
| Skin Sens. 1B | Skin sensitisation, category 1B |
| STOT RE 1 | Specific target organ toxicity — Repeated exposure, Category 1 |
| STOT RE 2 | Specific target organ toxicity — Repeated exposure, Category 2 |
| STOT SE 1 | Specific target organ toxicity — Single exposure, Category 1 |
| STOT SE 3 | Specific target organ toxicity — Single exposure, Category 3, |
| | Respiratory tract irritation |
| H226 | Flammable liquid and vapour. |
| H304 | May be fatal if swallowed and enters airways. |
| H312 | Harmful in contact with skin. |
| H314 | Causes severe skin burns and eye damage. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H332 | Harmful if inhaled. |
| H335 | May cause respiratory irritation. |
| H341 | Suspected of causing genetic defects. |
| H360 | May damage fertility or the unborn child. |

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| H370 | Causes damage to organs. |
|------|--|
| H372 | Causes damage to organs through prolonged or repeated exposure. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |

Abbreviations and Acronyms

ACGIH – American Conference of Governmental Industrial Hygienists ADN - European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road ATE - Acute Toxicity Estimate BCF - Bioconcentration Factor BEI - Biological Exposure Indices (BEI) BOD - Biochemical Oxygen Demand CAS No. - Chemical Abstracts Service Number CLP - Classification, Labeling and Packaging Regulation (EC) No 1272/2008 - Potential Hydrogen COD – Chemical Oxygen Demand EC – European Community EC50 - Median Effective Concentration FEC - European Economic Community SDS - Safety Data Sheet EINECS – European Inventory of Existing Commercial Chemical Substances EmS-No. (Fire) - IMDG Emergency Schedule Fire EmS-No. (Spillage) - IMDG Emergency Schedule Spillage EU – European Union ErC50 - EC50 in Terms of Reduction Growth Rate GHS – Globally Harmonized System of Classification and Labeling of Chemicals IARC - International Agency for Research on Cancer IATA - International Air Transport Association IBC Code - International Bulk Chemical Code IMDG - International Maritime Dangerous Goods IPRV - Ilgalaikio Poveikio Ribinis Dydis IOELV – Indicative Occupational Exposure Limit Value LC50 - Median Lethal Concentration LD50 - Median Lethal Dose LOAEL - Lowest Observed Adverse Effect Level LOEC - Lowest-Observed-Effect Concentration Log Koc - Soil Organic Carbon-water Partitioning Coefficient Log Kow - Octanol/water Partition Coefficient Log Pow - Ratio of the equilibrium concentration (C) of a dissolved substance in a twophase system consisting of two largely immiscible solvents, in this case octanol and water MAK - Maximum Workplace Concentration/Maximum Permissible Concentration MARPOL - International Convention for the Prevention of Pollution WGK - Wassergefährdungsklasse

NDS - Najwyzsze Dopuszczalne Stezenie NDSCh - Najwyzsze Dopuszczalne Stezenie Chwilowe NDSP - Najwyzsze Dopuszczalne Stezenie Pulapowe NOAEL - No-Observed Adverse Effect Level NOEC - No-Observed Effect Concentration NRD - Nevirsytinas Ribinis Dydis NTP – National Toxicology Program OEL - Occupational Exposure Limits PBT - Persistent, Bioaccumulative and Toxic PEL - Permissible Exposure Limit REACH – Registration, Evaluation, Authorisation, and Restriction of Chemicals RID – Regulations Concerning the International Carriage of Dangerous Goods by Rail SADT - Self Accelerating Decomposition Temperature STEL - Short Term Exposure Limit STOT - Specific Target Organ Toxicity TA-Luft - Technische Anleitung zur Reinhaltung der Luft TEL TRK – Technical Guidance Concentrations ThOD – Theoretical Oxygen Demand TLM - Median Tolerance Limit TLV - Threshold Limit Value TPRD - Trumpalaikio Poveikio Ribinis Dydis TRGS 510 - Technische Regel für Gefahrstoffe 510 - Lagerung von Gefahrstoffen in ortsbeweglichen Behältern TRGS 552 – Technische Regeln für Gefahrstoffe - N-Nitrosamine TRGS 900 - Technische Regel für Gefahrstoffe 900 – Arbeitsplatzgrenzwerte TRGS 903 - Technische Regel für Gefahrstoffe 903 - Biologische Grenzwerte TSCA - Toxic Substances Control Act TWA - Time Weighted Average VOC – Volatile Organic Compounds VLA-EC - Valor Límite Ambiental Exposición de Corta Duración VLA-ED - Valor Límite Ambiental Exposición Diaria VLE – Valeur Limite D'exposition VME – Valeur Limite De Moyenne Exposition vPvB - Very Persistent and Very Bioaccumulative WEL – Workplace Exposure Limit

Nusil EU GHS SDS

The information provided in this Safety Data Sheet (SDS) was prepared based on data believed to be accurate as of the date of this SDS. TO THE GREATEST EXTENT PERMITTED BY LAW, NUSIL TECHNOLOGY LLC AND ITS AFFILIATED COMPANIES ("NUSIL") EXPRESSLYDISCLAIMS ANY AND ALL REPRESENTATIONS AND WARRANTIES REGARDING THE INFORMATION CONTAINED HEREIN INCLUDING, WITHOUT LIMITATION, AS TO ACCURACY, COMPLETENESS, FITNESS FOR PURPOSE OR USE, MERCHANTABILITY, NON-INFRINGEMENT, PERFORMANCE, SAFETY, SUITABILITY AND STABILITY. This SDS is intended as a guide to the appropriate use, handling, storage and disposal of the product to which it relates by properly trained personnel, and is not intended to be comprehensive. Users of NuSil's products are advised to perform their own tests and to exercise their own judgment to determine the safety, suitability and appropriate use, handling, storage and disposal of each product and product combination for their own purposes and uses. TO THE GREATEST EXTENT PERMITTED BY LAW, NUSIL DISCLAIMS LIABILITY FOR, AND BY USING NUSIL'S PRODUCTS PURCHASER AGREES THAT UNDER NO CIRCUMSTANCES SHALL NUSIL BE LIABLE FOR, SPECIAL, INDIRECT, INCIDENTAL, PUNITIVE OR CONSEQUENTIAL DAMAGES OF ANY TYPE OR KIND, INCLUDING WITHOUT LIMITATION, FOR LOSS OF PROFITS, REPUTATIONAL DAMAGE, PRODUCT RECALL OR BUSINESS INTERRUPTION.



Silicone Sales & Services UK - Ireland - Benelux

© 2022 - Polymer Systems Technology Limited™ Unit 2. Network 4. Cressex Business Park, Lincoln Road, High Wycombe, Bucks. HP12 3RF

tel: +44 (0) 1494 446610

web: https://www.silicone-polymers.com

email: sales@silicone-polymers.co.uk

