

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Revision date: 26/08/2020 Date of issue: 17/04/2015

Version: 4.0

SECTION 1: Identification of the Substance/mixture and of the Company/Undertaking

Product Identifier 1.1.

Product form Mixture Product Name R-1008-6 Synonyms Silicone Ink

Relevant Identified Uses of the Substance or Mixture and Uses Advised Against 1.2.

1.2.1. Relevant Identified Uses

Use of the Substance/Mixture For professional use only.

1.2.2. Uses Advised Against

No additional information available

Details of the Supplier of the Safety Data Sheet

NuSil Technology Europe 1198 Avenue Maurice Donat Le Natura Bt. 2 06250 Mouains France +33 4 92 96 93 31

ehs@nusil.com

www.nusil.com

Emergency Telephone Number

Emergency Number : 800-424-9300 CHEMTREC (in US); +1 703-527-3887 CHEMTREC

(International and Maritime)

+(44)-870-8200418 +(353)-19014670)

SECTION 2: Hazards Identification

Classification of the Substance or Mixture

Classification According to Regulation (EC) No. 1272/2008 [CLP]

Flam. Lia. 3 H226 Skin Irrit. 2 H315 Eye Irrit. 2 H319 Skin Sens. 1 H317 STOT SE 3 H335 STOT RE 2 H373 Asp. Tox. 1 H304

Full text of hazard classes and H-statements: see section 16

2.2. **Label Elements**

Labelling According to Regulation (EC) No. 1272/2008 [CLP]

Hazard Pictograms (CLP)

GHS02

GHS07

Danger

Signal Word (CLP)

26/08/2020 EN (English) 1/18

Hazardous	lo aro dio ata
$\mathbf{H}(1)/(1)/(1)$	INGIAGIANIS

2-Butanone, O,O',O''-(methylsilylidyne)trioxime; Dibutyltin dilaurate; Reaction mass of ethylbenzene and xylene

Hazard Statements (CLP)

H226 - Flammable liquid and vapour.

H304 - May be fatal if swallowed and enters airways.

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

H335 - May cause respiratory irritation.

H373 - May cause damage to organs (blood) through prolonged or repeated exposure (oral).

Precautionary Statements (CLP)

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 - Keep container tightly closed.

P240 - Ground and bond container and receiving equipment.

P241 - Use explosion-proof electrical, ventilating, and lighting equipment.

P242 - Use non-sparking tools.

P243 - Take action to prevent static discharges.

P260 - Do not breathe mist, spray, vapours

P264 - Wash hands, forearms, and exposed areas thoroughly after handling

P270 - Do not eat, drink or smoke when using this product

P271 - Use only outdoors or in a well-ventilated area.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P280 - Wear eye protection, protective clothing, protective gloves

P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor

P302+P352 - IF ON SKIN: Wash with plenty of water

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 - Call a POISON CENTRE or doctor if you feel unwell.

P321 - Specific treatment (see Section 4 on this SDS)

P330 - Rinse mouth.

P331 - Do NOT induce vomiting.

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before

P370+P378 - In case of fire: Use appropriate media (see section 5) to extinguish

P403+P233+P235 - Store in a well-ventilated place. Keep

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

container tightly closed. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other Hazards

Other Hazards Not Contributing to the Classification

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

SECTION 3: Composition/Information on Ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product Identifier	%	Classification According to Regulation (EC) No. 1272/2008 [CLP]
Chromium oxide (Cr2O3)	(CAS-No.) 1308-38-9 (EC-No.) 215-160-9	20 - 30	Not classified
Reaction mass of ethylbenzene and xylene	(CAS-No.) Not Applicable (REACH Registration No.) 01-2119539452-40-0053 (EC-No.) 905-588-0	10 - 30	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
2-Butanone, O,O',O"- (methylsilylidyne)trioxime	(CAS-No.) 22984-54-9 (EC-No.) 245-366-4	< 15	Eye Irrit. 2, H319 Skin Sens. 1B, H317 STOT RE 2, H373
Dibutyltin dilaurate	(CAS-No.) 77-58-7 (EC-No.) 201-039-8 (EC Index-No.) 050-030-00-3	< 0.3	Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Muta. 2, H341 Repr. 1B, H360 STOT SE 1, H370 STOT RE 1, H372 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H-statements: see section 16

SECTION 4: First Aid Measures

4.1. Description of First-aid Measures

First-Aid Measures General

Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

26/08/2020 EN (English) 3/18

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

according to Regulation [Ee] No. 1707/2000 [RE/Reit] Will his amendment Regulation [E0] 2010/000		
First-Aid Measures After Inhalation	When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.	
First-Aid Measures After Skin Contact	Immediately remove contaminated clothing. Obtain medical attention if irritation/rash develops or persists. Immediately drench affected area with water for at least 15 minutes.	
First-Aid Measures After Eye Contact	Immediately rinse with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.	
First-Aid Measures After	Do NOT induce vomiting. Rinse mouth. Immediately call a	

POISON CENTER or doctor/physician. Ingestion 4.2.

Most Important Symptoms and Effects Both Acute and Delayed Symptoms/Effects

May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure. Skin sensitisation. Causes skin irritation. Causes serious eye irritation. May be fatal

if swallowed and enters airways.

May cause irritation to the respiratory tract, sneezing, coughing, Symptoms/Effects After Inhalation

burning sensation of throat with constricting sensation of the

larynx and difficulty in breathing

May cause an allergic skin reaction. Redness, pain, swelling, Symptoms/Effects After Skin

itching, burning, dryness, and dermatitis. Contact

Contact causes severe irritation with redness and swelling of the Symptoms/Effects After Eye Contact

conjunctiva.

Symptoms/Effects After Aspiration into the lungs can occur during ingestion or vomiting

and may cause lung injury.

Chronic Symptoms May cause damage to organs (blood) through prolonged or

repeated exposure (Oral).

Indication of Any Immediate Medical Attention and Special Treatment Needed 4.3. If exposed or concerned, get medical advice and attention. If medical advice is needed, have

product container or label at hand.

SECTION 5: Firefighting Measures

Extinguishing Media

Ingestion

Suitable Extinguishing Media Dry chemical powder, alcohol-resistant foam, carbon dioxide

(CO₂). Water may be ineffective but water should be used to

keep fire-exposed container cool.

Do not use a heavy water stream. A heavy water stream may Unsuitable Extinguishing Media

spread burning liquid.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard Flammable liquid and vapour.

Explosion Hazard May form flammable or explosive vapour-air mixture.

Reactivity Reacts violently with strong oxidisers. Increased risk of fire or

explosion.

Hazardous Decomposition Products in Case of Fire

Silicon oxides. Carbon oxides (CO, CO₂). Metal oxides. Oxides of tin.

Advice for Firefighters 5.3.

Precautionary Measures Fire Exercise caution when fighting any chemical fire.

Firefighting Instructions Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire

remotely due to the risk of explosion.

26/08/2020 EN (English) 4/18

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Protection During Firefighting Do not enter fire area without proper protective equipment,

including respiratory protection.

Other Information Do not allow run-off from fire fighting to enter drains or water

courses.

SECTION 6: Accidental Release Measures

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures Do not get in eyes, on skin, or on clothing. Keep away from

heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Use special care to avoid static electric

charges. Do not breathe vapor, mist or spray.

6.1.1. For Non-Emergency Personnel

Protective Equipment Use appropriate personal protective equipment (PPE). Emergency Procedures Evacuate unnecessary personnel. Stop leak if safe to do so.

6.1.2. For Emergency Responders

Protective Equipment Equip cleanup crew with proper protection.

Emergency Procedures Upon arrival at the scene, a first responder is expected to

recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

Eliminate ignition sources.

6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment Contain any spills with dikes or absorbents to prevent migration

and entry into sewers or streams. As an immediate

precautionary measure, isolate spill or leak area in all directions.

Methods For Cleaning Up Clean up spills immediately and dispose of waste safely.

Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill. Absorb and/or contain spill with inert material. Do not take up in combustible material such as: saw dust or cellulosic material. Use only non-

sparking tools.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: Handling And Storage

7.1. Precautions for Safe Handling

Additional Hazards When

Processed

Handle empty containers with care because residual vapours are flammable.

Precautions for Safe Handling Wash hands and other exposed areas with mild soap and

water before eating, drinking or smoking and when leaving work. Take precautionary measures against static discharge. Use only non-sparking tools. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe vapours, mist, spray. Handle empty containers with care because they may still present a

hazard. Do not get in eyes, on skin, or on clothing.

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hygiene Measures Handle in accordance with good industrial hygiene and safety

procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures Comply with applicable regulations. Take action to prevent

static discharges. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, and

lighting equipment.

Storage Conditions Store in a dry, cool place. Keep/Store away from direct sunlight,

extremely high or low temperatures and incompatible materials. Store locked up/in a secure area. Store in a well-ventilated place. Keep container tightly closed. Keep in

fireproof place.

Incompatible Materials Strong acids, strong bases, strong oxidizers.

7.3. Specific End Use(S)

As a marking ink for silicone rubber parts and other components where the coating must maintain long term stability. For professional use only.

SECTION 8: Exposure Controls/Personal Protection

8.1. Control Parameters

Tin organic compound	ds	
Austria	MAK (mg/m³)	0,1 mg/m³ (except tri-n-Butyltin compounds-inhalable fraction)
Austria	MAK Short time value (mg/m³)	0,2 mg/m³ (except Tri-n-butyltin compounds-inhalable fraction)
Austria	OEL chemical category (AT)	Skin notation except Tri-n-butyItin compounds
Belgium	Limit value (mg/m³)	0,1 mg/m³
Belgium	Short time value (mg/m³)	0,2 mg/m³
Belgium	OEL chemical category (BE)	Skin
Bulgaria	OEL TWA (mg/m³)	0,1 mg/m³
Croatia	GVI (granična vrijednost izloženosti) (mg/m³)	0,1 mg/m³ (except Cyhexatin)
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (mg/m³)	0,2 mg/m³ (except Cyhexatin)
Czech Republic	Expoziční limity (PEL) (mg/m³)	0,1 mg/m³
Czech Republic	OEL chemical category (CZ)	Potential for cutaneous absorption
Denmark	Grænsevædi (8 timer) (mg/m³)	0,1 mg/m³ (except Tri-n-butyltin compounds)
Estonia	OEL TWA (mg/m³)	0,1 mg/m³
Estonia	OEL STEL (mg/m³)	0,2 mg/m³
Estonia	OEL chemical category (ET)	Skin notation
Finland	HTP-arvo (8h) (mg/m³)	0,1 mg/m³
Finland	HTP-arvo (15 min)	0,3 mg/m³
Finland	OEL chemical category (FI)	Potential for cutaneous absorption
France	VLE (mg/m³)	0,2 mg/m³
France	VME (mg/m³)	0,1 mg/m³
Greece	OEL TWA (mg/m³)	0,1 mg/m³

26/08/2020 EN (English) 6/18

Greece	OEL STEL (mg/m³)	0,2 mg/m³
Greece	OEL chemical category (GR)	skin - potential for cutaneous
		absorption
Hungary	AK-érték	0,1 mg/m³
Hungary	CK-érték	0,4 mg/m³
Hungary	OEL chemical category (HU)	Potential for cutaneous absorption
Ireland	OEL (8 hours ref) (mg/m³)	0,1 mg/m³
Ireland	OEL (15 min ref) (mg/m3)	0,2 mg/m³
Lithuania	IPRV (mg/m³)	0,1 mg/m³
Lithuania	TPRV (mg/m³)	0,2 mg/m³
Lithuania	OEL chemical category (LT)	Skin notation
Norway	Grenseverdier (AN) (mg/m³)	0,1 mg/m³
Norway	Grenseverdier (Korttidsverdi)	
	(mg/m3)	0,3 mg/m³ (value calculated)
Norway	OEL chemical category (NO)	Skin notation
Portugal	OEL TWA (mg/m³)	0,1 mg/m³
Portugal	OEL STEL (mg/m³)	0,2 mg/m³
Portugal	OEL chemical category (PT)	A4 - Not Classifiable as a Human
		Carcinogen,skin - potential for
	051 7044 (2)	cutaneous exposure
Romania	OEL TWA (mg/m³)	0,05 mg/m³
Romania	OEL STEL (mg/m³)	0,15 mg/m³
Slovakia	NPHV (priemerná) (mg/m³)	0,1 mg/m³
Slovakia	NPHV (Hraničná) (mg/m³)	0,2 mg/m³
Slovakia	OEL chemical category (SK)	Potential for cutaneous absorption
Spain	VLA-ED (mg/m³)	0,1 mg/m³
Spain	VLA-EC (mg/m³)	0,2 mg/m³
Spain	OEL chemical category (ES)	skin - potential for cutaneous absorption
Sweden	nivågränsvärde (NVG)	
	(mg/m³)	0,1 mg/m³ (total dust)
Sweden	kortidsvärde (KTV) (mg/m³)	0,2 mg/m³ (total dust)
Sweden	OEL chemical category (SE)	Skin notation
Switzerland	KZGW (mg/m³)	0,2 mg/m³ (inhalable dust)
Switzerland	MAK (mg/m³)	0,1 mg/m³ (inhalable dust)
Switzerland	OEL chemical category (CH)	Skin notation
United Kingdom	WEL TWA (mg/m³)	0,1 mg/m³ (except Cyhexatin)
United Kingdom	WEL STEL (mg/m³)	0,2 mg/m³ (except Cyhexatin)
United Kingdom	WEL chemical category	Potential for cutaneous absorption except Cyhexatin
Chromium oxide (Cr2O3) (1	308-38-9)	
Estonia	OEL TWA (mg/m³)	0,02 mg/m ³
Estonia	OEL STEL (mg/m³)	0,06 mg/m³
Estonia	OEL chemical category (ET)	Carcinogenic substance, Sensitizer
Latvia	OEL TWA (mg/m³)	1 mg/m³

	2006 (REACH) with its amendment Regulation (EU) 2015/830	
	nylbenzene and xylene No.) 01-2119539452-40-0053	
EU	IOELV TWA (mg/m³)	221 mg/m³ (pure)
EU	IOELV TWA (mg/m)	50 ppm (pure)
EU	IOELV STEL (mg/m³)	442 mg/m³ (pure)
EU	IOELV STEL (ING/III)	100 ppm (pure)
EU	Notes	Possibility of significant uptake
LU	140163	through the skin (pure)
Austria	MAK (mg/m³)	221 mg/m³ (all isomers)
Austria	MAK (ppm)	50 ppm (all isomers)
Austria	MAK Short time value (mg/m³)	442 mg/m³
Austria	MAK Short time value (ppm)	100 ppm
Belgium	Limit value (mg/m³)	221 mg/m³
Belgium	Limit value (ppm)	50 ppm
Belgium	Short time value (mg/m³)	442 mg/m³
Belgium	Short time value (ppm)	100 ppm
Belgium	OEL chemical category (BE)	Skin, Skin notation pure
Bulgaria	OEL TWA (mg/m³)	221 mg/m³ (pure)
Bulgaria	OEL TWA (ppm)	50 ppm (pure)
Bulgaria	OEL STEL (mg/m³)	442 mg/m³ (pure)
Bulgaria	OEL STEL (ppm)	100 ppm (pure)
Croatia	GVI (granična vrijednost izloženosti) (mg/m³)	221 mg/m³
Croatia	GVI (granična vrijednost izloženosti) (ppm)	50 ppm
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (mg/m³)	442 mg/m³
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (ppm)	100 ppm
Croatia	OEL chemical category (HR)	Skin notation
Croatia	Croatia - BLV	1,5 mg/l Parameter: Xylene - Medium: blood - Sampling time: at the end of the work shift (alcohol before exposure to Xylene raises occurrence) 1,5 g/g creatinine Parameter: Methylhippuric acid - Medium: urine - Sampling time: at the end of the work shift (calculated on the average Creatinine value of 1.2 g/L urine)
Cyprus	OEL TWA (mg/m³)	221 mg/m³
Cyprus	OEL TWA (ppm)	50 ppm
Cyprus	OEL STEL (mg/m³)	442 mg/m³
Cyprus	OEL STEL (ppm)	100 ppm
Cyprus	OEL chemical category (CY)	Skin-potential for cutaneous absorption

	with its amendment Regulation (EU) 2015/830	1000
Czech Republic	Expoziční limity (PEL) (mg/m³)	200 mg/m³
Czech Republic	OEL chemical category (CZ)	Potential for cutaneous absorption
Czech Republic	Czech Republic - BLV	820 µmol/mmol Creatinine Parameter: Methylhippuric acid - Medium: urine - Sampling time: end of shift 1400 mg/g creatinine Parameter: Methylhippuric acid - Medium: urine - Sampling time: end of shift
Denmark	Grænsevædi (8 timer)	
Deninark	(mg/m³)	109 mg/m³ (Xylene, all isomers)
Denmark	Grænsevædi (8 timer) (ppm)	25 ppm (Xylene, all isomers)
Estonia	OEL TWA (mg/m³)	200 mg/m³
Estonia	OEL TWA (ppm)	50 ppm
Estonia	OEL STEL (mg/m³)	450 mg/m³
Estonia	OEL STEL (ppm)	100 ppm
Estonia	OEL chemical category (ET)	Skin notation
Finland	HTP-arvo (8h) (mg/m³)	220 mg/m³
Finland	HTP-arvo (8h) (ppm)	50 ppm
Finland	HTP-arvo (15 min)	440 mg/m³
Finland	HTP-arvo (15 min) (ppm)	100 ppm
Finland	OEL chemical category (FI)	Potential for cutaneous absorption
Finland	Finland - BLV	Parameter: Methylhippuric acid - Medium: urine - Sampling time: after the shift
France	VLE (mg/m³)	442 mg/m³ (restrictive limit)
France	VLE (ppm)	100 ppm (restrictive limit)
France	VME (mg/m³)	221 mg/m³ (restrictive limit)
France	VME (ppm)	50 ppm (restrictive limit)
France	OEL chemical category (FR)	Risk of cutaneous absorption
France	France - BLV	1500 mg/g creatinine Parameter: Methylhippuric acid - Medium: urine - Sampling time: end of shift
Germany	Occupational exposure limit value (mg/m³)	440 mg/m³ (all isomers)
Germany	Occupational exposure limit value (ppm)	100 ppm (all isomers)
Germany	TRGS 903 Biological limit value	2000 mg/l Parameter: Methylhippuric(tolur-)acid (all isomers) - Medium: urine - Sampling time: end of shift (all isomers)
Germany	Chemical category	Skin notation all isomers
Gibraltar	Eight hours mg/m3	221 mg/m³ (pure)
Gibraltar	Eight hours ppm	50 ppm (pure)
Gibraltar	Short-term mg/m3	442 mg/m³ (pure)
Gibraltar	Short-term ppm	100 ppm (pure)
Gibraltar	OEL chemical category (GI)	Skin notation pure

Recording to Regulation (Ee) No. 1707/200	06 (REACH) with its amendment Regulation (EU) 2015/830	
Greece	OEL TWA (mg/m³)	435 mg/m³
Greece	OEL TWA (ppm)	100 ppm
Greece	OEL STEL (mg/m³)	650 mg/m³
Greece	OEL STEL (ppm)	150 ppm
Greece	OEL chemical category (GR)	skin - potential for cutaneous
		absorption
Hungary	AK-érték	221 mg/m³
Hungary	CK-érték	442 mg/m³
Hungary	OEL chemical category (HU)	Potential for cutaneous absorption
Ireland	OEL (8 hours ref) (mg/m³)	221 mg/m³
Ireland	OEL (8 hours ref) (ppm)	50 ppm
Ireland	OEL (15 min ref) (mg/m3)	442 mg/m³
Ireland	OEL (15 min ref) (ppm)	100 ppm
Ireland	OEL chemical category (IE)	Potential for cutaneous absorption
Italy	OEL TWA (mg/m³)	221 mg/m³ (pure)
Italy	OEL TWA (ppm)	50 ppm (pure)
Italy	OEL STEL (mg/m³)	442 mg/m³ (pure)
Italy	OEL STEL (ppm)	100 ppm (pure)
Italy	OEL chemical category (IT)	skin - potential for cutaneous
		absorption pure
Latvia	OEL TWA (mg/m³)	221 mg/m³
Latvia	OEL TWA (ppm)	50 ppm
Latvia	OEL chemical category (LV)	skin - potential for cutaneous exposure
Lithuania	IPRV (mg/m³)	221 mg/m³ (mixed isomers, pure)
Lithuania	IPRV (ppm)	50 ppm (mixed isomers, pure)
Lithuania	TPRV (mg/m³)	442 mg/m³ (mixed isomers, pure)
Lithuania	TPRV (ppm)	100 ppm (mixed isomers, pure)
Lithuania	OEL chemical category (LT)	Skin notation
Luxembourg	OEL TWA (mg/m³)	221 mg/m³
Luxembourg	OEL TWA (ppm)	50 ppm
Luxembourg	OEL STEL (mg/m³)	442 mg/m³
Luxembourg	OEL STEL (ppm)	100 ppm
Luxembourg	OEL chemical category (LU)	Possibility of significant uptake through the skin
Malta	OEL TWA (mg/m³)	221 mg/m³ (pure)
Malta	OEL TWA (ppm)	50 ppm (pure)
Malta	OEL STEL (mg/m³)	442 mg/m³ (pure)
Malta	OEL STEL (ppm)	100 ppm (pure)
Malta	OEL chemical category (MT)	Possibility of significant uptake through the skin pure
Netherlands	Grenswaarde TGG 8H (mg/m³)	210 mg/m³
Netherlands	Grenswaarde TGG 15MIN (mg/m³)	442 mg/m³

Grenseverdier (AN) (mg/m³)	108 mg/m³
Grenseverdier (AN) (ppm)	25 ppm
Grenseverdier (Korttidsverdi)	
	135 mg/m³ (value calculated)
Grenseverdier (Korttidsverdi)	
	37,5 ppm (value calculated)
	Skin notation
	100 mg/m³ (mixture of isomers)
	200 mg/m³ (mixture of isomers)
, , ,	221 mg/m³ (indicative limit value)
OEL TWA (ppm)	50 ppm (indicative limit value)
OEL STEL (mg/m³)	442 mg/m³ (indicative limit value)
OEL STEL (ppm)	100 ppm (indicative limit value)
OEL chemical category (PT)	A4 - Not Classifiable as a Human Carcinogen
OEL TWA (mg/m³)	221 mg/m³ (pure)
OEL TWA (ppm)	50 ppm (pure)
OEL STEL (mg/m³)	442 mg/m³ (pure)
OEL STEL (ppm)	100 ppm (pure)
OEL chemical category (RO)	Skin notation pure
Romania - BLV	3 g/l Parameter: Methylhippuric acid - Medium: urine - Sampling time: end of shift
NPHV (priemerná) (mg/m³)	221 mg/m³
NPHV (priemerná) (ppm)	50 ppm
NPHV (Hraničná) (mg/m³)	442 mg/m³
OEL chemical category (SK)	Potential for cutaneous absorption
Slovakia - BLV	1,5 mg/l Parameter: Xylene - Medium: blood - Sampling time: end of exposure or work shift (all isomers) 2000 mg/l Parameter: Methylhippuric acid - Medium: urine - Sampling time: end of exposure or work shift
OEL TWA (mg/m³)	221 mg/m³
OEL TWA (ppm)	50 ppm
OEL STEL (mg/m³)	442 mg/m³
OEL STEL (ppm)	100 ppm
OEL chemical category (SI)	Potential for cutaneous absorption
VLA-ED (mg/m³)	221 mg/m³ (indicative limit value)
VLA-ED (ppm)	50 ppm (indicative limit value)
VLA-EC (mg/m³)	442 mg/m³
VLA-EC (ppm)	100 ppm
OEL chemical category (ES)	skin - potential for cutaneous absorption
	Grenseverdier (Korttidsverdi) (mg/m3) Grenseverdier (Korttidsverdi) (ppm) OEL chemical category (NO) NDS (mg/m³) NDSCh (mg/m³) OEL TWA (mg/m³) OEL STEL (mg/m³) OEL STEL (ppm) OEL STEL (ppm) OEL TWA (ppm) OEL STEL (mg/m³) OEL TWA (ppm) OEL STEL (mg/m³) OEL STEL (mg/m³) OEL STEL (mg/m³) OEL STEL (ppm) OEL STEL (ppm) OEL chemical category (RO) Romania - BLV NPHV (priemerná) (mg/m³) NPHV (priemerná) (ppm) NPHV (Hraničná) (mg/m³) OEL chemical category (SK) Slovakia - BLV OEL TWA (ppm) OEL STEL (mg/m³) OEL STEL (mg/m³) OEL STEL (mg/m³) OEL STEL (mg/m³) OEL STEL (ppm) OEL Chemical category (SI) VLA-ED (mg/m³) VLA-ED (ppm) VLA-EC (mg/m³) VLA-EC (ppm)

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Spain	Spain - BLV	1 g/g creatinine Parameter: Methylhippuric acids - Medium: urine - Sampling time: end of shift
Sweden	nivågränsvärde (NVG) (mg/m³)	221 mg/m³ (Xylene)
Sweden	nivågränsvärde (NVG) (ppm)	50 ppm (Xylene)
Sweden	kortidsvärde (KTV) (mg/m³)	442 mg/m³ (Xylene)
Sweden	kortidsvärde (KTV) (ppm)	100 ppm (Xylene)
Sweden	OEL chemical category (SE)	Skin notation
Switzerland	KZGW (mg/m³)	870 mg/m³
Switzerland	KZGW (ppm)	200 ppm
Switzerland	MAK (mg/m³)	435 mg/m³
Switzerland	MAK (ppm)	100 ppm
Switzerland	OEL chemical category (CH)	Skin notation
Switzerland	Switzerland - BLV	2 g/l Parameter: Methylhippuric acid - Medium: urine - Sampling time: end of shift
United Kingdom	WEL TWA (mg/m³)	220 mg/m³
United Kingdom	WEL TWA (ppm)	50 ppm
United Kingdom	WEL STEL (mg/m³)	441 mg/m³
United Kingdom	WEL STEL (ppm)	100 ppm
United Kingdom	WEL chemical category	Potential for cutaneous absorption

8.2. Exposure Controls

Appropriate Engineering Controls

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Gas detectors should be used when flammable gases or vapors may be released. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment. Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.

Personal Protective Equipment









Materials for Protective Clothing

resistant/retardant clothing. Wear protective gloves.

Hand Protection
Eye Protection

Chemical safety goggles.

Skin and Body Protection Respiratory Protection Wear suitable protective clothing.

If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory

Chemically resistant materials and fabrics. Wear fire/flame

protection.

Other Information When using, do not eat, drink or smoke.

26/08/2020 EN (English) 12/18

SECTION 9: Physical and Chemical Hazards

9.1. Information on Basic Physical and Chemical Properties

Physical State Liquid
Colour Green
Odour Solvent

Odour Threshold

pH

No data available

Evaporation Rate

Melting Point

No data available

140 °C (284 °F)

Flash Point

27 °C (81 °F)

Auto-Ignition Temperature

Decomposition Temperature

Flammability (Solid, Gas)

Vapour Pressure

Relative Vapour Density At 20 °C

No data available

No data available

No data available

Specific Gravity > 1

Relative Density No data available Solubility No data available Partition Coefficient n-Octanol/Water No data available Viscosity, Kinematic No data available Viscosity, Dynamic No data available **Explosive Properties** No data available Oxidising Properties No data available **Explosive Limits** No data available

9.2. Other Information

VOC content 10 - 30 %

SECTION 10: Stability and Reactivity

10.1. Reactivity

Reacts violently with strong oxidisers. Increased risk of fire or explosion.

10.2. Chemical Stability

Flammable liquid and vapour. May form flammable or explosive vapour-air mixture.

10.3. Possibility Of Hazardous Reactions

Hazardous polymerization will not occur.

10.4. Conditions To Avoid

Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.

10.5. Incompatible Materials

Strong acids, strong bases, strong oxidizers.

10.6. Hazardous Decomposition Products

None expected under normal conditions of use.

SECTION 11: Toxicological Information

11.1. Information On Toxicological Effects

Acute Toxicity Not classified (Based on available data, the classification

criteria are not met)

R-1008-6	
ATE CLP (oral)	2000 mg/kg bodyweight
Dibutyltin dilaurate (77-58-7)	
LD50 Oral	175 mg/kg
LD50 Dermal Rat	> 2 g/kg
2-Butanone, O,O',O"-(methylsilyli	dyne)trioxime (22984-54-9)
LD50 Oral Rat	2463 mg/kg
LD50 Dermal Rat	> 2000 mg/kg
Chromium oxide (Cr2O3) (1308-3	38-9)
LD50 Oral Rat	> 5000 mg/kg
Reaction mass of ethylbenzene (REACH Registration No.) 01-2119	
LD50 Oral Rat	3523 mg/kg
LC50 Inhalation Rat	6700 ppm/4h
ATE CLP (oral)	3523 mg/kg bodyweight
ATE CLP (dermal)	1100 mg/kg bodyweight
ATE CLP (gases)	6700 ppmv/4h
ATE CLP (vapours)	11 mg/l/4h
Skin Corrosion/Irritation	Causes skin irritation.

Eye Damage/Irritation

Respiratory or Skin Sensitization

Germ Cell Mutagenicity

Jauses skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

Not classified (Based on available data, the classification

criteria are not met)

Not classified (Based on available data, the classification Carcinogenicity

criteria are not met)

Reproductive Toxicity Not classified (Based on available data, the classification

criteria are not met)

Specific Target Organ Toxicity

(Single Exposure)

May cause respiratory irritation.

May cause damage to organs (blood) through

prolonged or repeated exposure (oral).

Aspiration Hazard May be fatal if swallowed and enters airways.

SECTION 12: Ecological Information

Specific Target Organ Toxicity (Repeated

12.1. Toxicity

Exposure)

Ecology - General Toxic to aquatic life.

Dibutyltin dilaurate (77-58-7)	
EC50 Daphnia 1 0,463 mg/l (Daphnia magna)	
2-Butanone, O,O',O"-(methylsilylidyne)trioxime (22984-54-9)	
EC50 Daphnia 1 120 mg/l (Exposure time: 48h - Species: Daphnia magna)	

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Chromium oxide (Cr2O3) (1308-38-9)		
LC50 Fish 1 > 10000 mg/l (Exposure time: 96 h - Species: Danio rerio [sta		
NOEC Chronic Fish	1000 mg/l (Species: Brachydanio rerio - Duration: 30 d)	

12.2. Persistence and Degradability

R-1008-6	
Persistence and Degradability	Not established.

12.3. Bioaccumulative Potential

R-1008-6		
Bioaccumulative potential Not established.		
Dibutyltin dilaurate (77-58-7)		
Log Pow	4,44	

12.4. Mobility in Soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other Adverse Effects

Other Information Avoid release to the environment.

SECTION 13: Disposal Considerations

13.1. Waste Treatment Methods

Product/Packaging Disposal Dispose of contents/container in accordance with local,

Recommendations regional, national, and international regulations.

Additional Information Handle empty containers with care because residual vapours

are flammable.

the aquatic environment. Keep out of sewers and waterways.

SECTION 14: Transport Information

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN Number				
1307	1307	1307	1307	1307
14.2. UN Proper Shipping Name				
XYLENES	XYLENES	XYLENES	XYLENES	XYLENES
SOLUTION	SOLUTION	SOLUTION	SOLUTION	SOLUTION
14.3. Transport Hazard Class(Es)				
3	3	3	3	3
3		3	3	3
14.4. Packing Group				
III	III	III	III	

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ADR	IMDG	IATA	ADN	RID
14.5. Environmental Hazards				
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No

14.6. Special Precautions For User

No additional information available

14.7. Transport in Bulk According to Annex II of MARPOL and The IBC Code

Not applicable

SECTION 15: Regulatory Information

15.1. Safety, Health and Environmental Regulations/Legislation Specific for the Substance or Mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions Contains no substance on the REACH candidate list Contains no REACH Annex XIV substances

15.1.2. National Regulations

No additional information available

15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out

SECTION 16: Other Information

Indication of Changes

Section	Section Header	Change	Date Changed
1	Identification of the substance/mixture and of the	Modified	26/08/2020
	company/undertaking		
2	Hazards identification	Modified	26/08/2020
3	Composition/information on ingredients	Modified	26/08/2020
4	First aid measures	Modified	26/08/2020
8	Exposure controls/personal protection	Modified	26/08/2020
9	Physical and chemical properties	Modified	26/08/2020
10	Stability and reactivity	Modified	26/08/2020
11	Toxicological information	Modified	26/08/2020

Date of Preparation or Latest

Revision

Data Sources

26/08/2020

Information and data obtained and used in the authoring of this safety data sheet could come from database subscriptions,

official government regulatory body websites,

product/ingredient manufacturer or supplier specific

information, and/or resources that include substance specific data and classifications according to GHS or their subsequent

adoption of GHS.

Other Information

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Full Text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4	
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4	
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4	
Aquatic Acute 1	Hazardous to the aquatic environment — Acute	
	Hazard, Category 1	
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic	
	Hazard, Category 1	
Asp. Tox. 1	Aspiration hazard, Category 1	
Eye Dam. 1	Serious eye damage/eye irritation, Category 1	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
Flam. Liq. 3	Flammable liquids, Category 3	
Muta. 2	Germ cell mutagenicity, Category 2	
Repr. 1B	Reproductive toxicity, Category 1B	
Skin Corr. 1C	Skin corrosion/irritation, Category 1C	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
Skin Sens. 1	Skin sensitisation, Category 1	
Skin Sens. 1B	Skin sensitisation, category 1B	
STOT RE 1	Specific target organ toxicity — Repeated exposure,	
	Category 1	
STOT RE 2	Specific target organ toxicity — Repeated exposure,	
	Category 2	
STOT SE 1	Specific target organ toxicity — Single exposure,	
CTOT CF 2	Category 1	
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation	
H226	Flammable liquid and vapour.	
H304	May be fatal if swallowed and enters airways.	
H312	Harmful in contact with skin.	
H314	Causes severe skin burns and eye damage.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H319	Causes serious eye darriage. Causes serious eye irritation.	
H332	Harmful if inhaled.	
H335	May cause respiratory irritation.	
H341	Suspected of causing genetic defects.	
H360	May damage fertility or the unborn child.	
H370	Causes damage to organs.	
H372	Causes damage to organs through prolonged or	
	repeated exposure.	
H373	May cause damage to organs through prolonged or	
	repeated exposure.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Abbreviations and Acronyms

ACGIH - American Conference of Governmental Industrial Hygienists

ADN – European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

ATF - Acute Toxicity Estimate BCF - Bioconcentration Factor BEI - Biological Exposure Indices (BEI)

BOD - Biochemical Oxygen Demand CAS No. - Chemical Abstracts Service Number

CLP - Classification, Labeling and Packaging Regulation (EC) No 1272/2008

COD - Chemical Oxygen Demand

EC – European Community EC50 - Median Effective Concentration EEC - European Economic Community

EINECS – European Inventory of Existing Commercial Chemical Substances EmS-No. (Fire) - IMDG Emergency Schedule Fire

EmS-No. (Spillage) - IMDG Emergency Schedule Spillage

FU - Furopean Union

ErC50 - EC50 in Terms of Reduction Growth Rate

GHS – Globally Harmonized System of Classification and Labeling of Chemicals

IARC - International Agency for Research on Cancer IATA - International Air Transport Association IBC Code - International Bulk Chemical Code IMDG - International Maritime Dangerous Goods

IPRV - Ilgalaikio Poveikio Ribinis Dydis

IOELV - Indicative Occupational Exposure Limit Value

LC50 - Median Lethal Concentration

LD50 - Median Lethal Dose

LOAEL - Lowest Observed Adverse Effect Level LOEC - Lowest-Observed-Effect Concentration

Log Koc - Soil Organic Carbon-water Partitioning Coefficient

Log Kow - Octanol/water Partition Coefficient

Log Pow - Ratio of the equilibrium concentration (C) of a dissolved substance in a two-phase system consisting of two largely immiscible solvents, in this case octanol

MAK - Maximum Workplace Concentration/Maximum Permissible Concentration MARPOL - International Convention for the Prevention of Pollution

NDS - Naiwyzsze Dopuszczalne Stezenie

NDSCh - Najwyzsze Dopuszczalne Stezenie Chwilowe NDSP - Naiwyzsze Dopuszczalne Stezenie Pulapowe NOAEL - No-Observed Adverse Effect Level

NOEC - No-Observed Effect Concentration NRD - Nevirsytings Ribinis Dydis NTP – National Toxicology Program

OEL - Occupational Exposure Limits PBT - Persistent, Bioaccumulative and Toxic

PEL - Permissible Exposure Limit

pH – Potential Hydrogen

REACH – Registration, Evaluation, Authorisation, and Restriction of Chemicals RID – Regulations Concerning the International Carriage of Dangerous Goods by Rail

SADT - Self Accelerating Decomposition Temperature

SDS - Safety Data Sheet

STEL - Short Term Exposure Limit STOT - Specific Target Organ Toxicity

TA-Luft - Technische Anleitung zur Reinhaltung der Luft

TEL TRK - Technical Guidance Concentrations

ThOD – Theoretical Oxygen Demand TLM - Median Tolerance Limit

TPRD - Trumpalaikio Poveikio Ribinis Dydis

TRGS 510 - Technische Regel für Gefahrstoffe 510 - Lagerung von Gefahrstoffen in

ortsbeweglichen Behältern

TLV - Threshold Limit Value

TRGS 552 – Technische Regeln für Gefahrstoffe - N-Nitrosamine

TRGS 900 - Technische Regel für Gefahrstoffe 900 – Arbeitsplatzgrenzwerte TRGS 903 - Technische Regel für Gefahrstoffe 903 - Biologische Grenzwerte

TSCA - Toxic Substances Control Act

TWA - Time Weighted Average VOC – Volatile Organic Compounds

VLA-EC - Valor Límite Ambiental Exposición de Corta Duración

VLA-ED - Valor Límite Ambiental Exposición Diaria

VLE – Valeur Limite D'exposition

VME - Valeur Limite De Movenne Exposition

vPvB - Very Persistent and Very Bioaccumulative

WEL – Workplace Exposure Limit WGK - Wassergefährdungsklasse

Nusil EU GHS SDS

The information provided in this Safety Data Sheet (SDS) was prepared based on data believed to be accurate as of the date of this SDS. TO THE GREATEST EXTENT PERMITTED BY LAW, NUSIL TECHNOLOGY LLC AND ITS AFFILIATED COMPANIES ("NUSIL") EXPRESSLYDISCLAIMS ANY AND ALL REPRESENTATIONS AND WARRANTIES REGARDING THE INFORMATION CONTAINED HEREIN INCLUDING, WITHOUT LIMITATION, AS TO ACCURACY, COMPLETENESS, FITNESS FOR PURPOSE OR USE, MERCHANTABILITY, NON-INFRINGEMENT, PERFORMANCE, SAFETY, SUITABILITY AND STABILITY. This SDS is intended as a guide to the appropriate use, handling, storage and disposal of the product to which it relates by properly trained personnel, and is not intended to be comprehensive. Users of NuSil's products are advised to perform their own tests and to exercise their own judgment to determine the safety, suitability and appropriate use, handling, storage and disposal of each product and product combination for their own purposes and uses. TO THE GREATEST EXTENT PERMITTED BY LAW, NUSIL DISCLAIMS LIABILITY FOR, AND BY USING NUSIL'S PRODUCTS PURCHASER AGREES THAT UNDER NO CIRCUMSTANCES SHALL NUSIL BE LIABLE FOR. SPECIAL, INDIRECT, INCIDENTAL, PUNITIVE OR CONSEQUENTIAL DAMAGES OF ANY TYPE OR KIND. INCLUDING WITHOUT LIMITATION, FOR LOSS OF PROFITS, REPUTATIONAL DAMAGE, PRODUCT RECALL OR BUSINESS INTERRUPTION.

26/08/2020 EN (English) 18/18



Silicone Sales & Services UK - Ireland - Benelux

© 2022 - Polymer Systems Technology Limited™ Unit 2. Network 4. Cressex Business Park, Lincoln Road, High Wycombe, Bucks. HP12 3RF

tel: +44 (0) 1494 446610

web: https://www.silicone-polymers.com

email: sales@silicone-polymers.co.uk

